

1 System.DuplicateWaitObjectException

2 Class

3
4

```
5 [ILASM]  
6 .class public serializable DuplicateWaitObjectException  
7 extends System.ArgumentException  
  
8 [C#]  
9 public class DuplicateWaitObjectException:  
10 ArgumentException
```

11 Assembly Info:

- 12 • Name: mscorlib
- 13 • Public Key: [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- 14 • Version: 1.0.x.x
- 15 • Attributes:
 - 16 ○ CLSCompliantAttribute(true)

17 Summary

18

19 Represents the error that occurs when an object appears more than
20 once in an array of **System.Threading.WaitHandle** instances.

21 Inherits From: System.ArgumentException

22

23 **Library:** BCL

24

25 **Thread Safety:** All public static members of this type are safe for multithreaded
26 operations. No instance members are guaranteed to be thread safe.

27

28 Description

29 [Note: It is generally unnecessary for applications to throw
30 **System.DuplicateWaitObjectException**. This exception is thrown
31 by thread synchronization methods, such as
32 **System.Threading.WaitHandle.WaitAll** and
33 **System.Threading.WaitHandle.WaitAny**.]

34

1 DuplicateWaitObjectException() 2 Constructor

```
3 [ILASM]  
4 public rtspecialname specialname instance void .ctor()  
5 [C#]  
6 public DuplicateWaitObjectException()
```

7 Summary

8 Constructs and initializes a new instance of the
9 **System.DuplicateWaitObjectException** class.

10 Description

11 This constructor initializes the
12 **System.DuplicateWaitObjectException.Message** property of the
13 new instance to a system-supplied message that describes the error,
14 such as "Duplicate objects in argument." This message takes into
15 account the current system culture. The
16 **System.DuplicateWaitObjectException.InnerException** and
17 **System.DuplicateWaitObjectException.ParamName** properties
18 are initialized to **null**.

19

1 DuplicateWaitObjectException(System.String) Constructor

```
3 [ILASM]  
4 public rtspecialname specialname instance void .ctor(string  
5 parameterName)  
  
6 [C#]  
7 public DuplicateWaitObjectException(string parameterName)
```

8 Summary

9 Constructs and initializes a new instance of the
10 **System.DuplicateWaitObjectException** class.

11 Parameters

12
13

| Parameter | Description |
|----------------------|---|
| <i>parameterName</i> | A System.String that contains the name of the parameter that caused the exception. The content of <i>parameterName</i> is intended to be understood by humans. |

14
15

Description

16 This constructor initializes the
17 **System.DuplicateWaitObjectException.Message** property of the
18 new instance to a system-supplied message that describes the error.
19 This message takes into account the current system culture. The
20 **System.DuplicateWaitObjectException.InnerException** property
21 is initialized to **null**.

22
23
24
25

This constructor initializes the
System.DuplicateWaitObjectException.ParamName property of
the new instance using *parameterName*.

26

1 DuplicateWaitObjectException(System.String, System.String) Constructor

```
3 [ILASM]
4 public rtspecialname specialname instance void .ctor(string
5 parameterName, string message)
6
7 [C#]
8 public DuplicateWaitObjectException(string parameterName,
9 string message)
```

9 Summary

10 Constructs and initializes a new instance of the
11 **System.DuplicateWaitObjectException** class.

12 Parameters

13
14

| Parameter | Description |
|----------------------|---|
| <i>parameterName</i> | A System.String that contains the name of the parameter that caused the exception. The content of <i>parameterName</i> is intended to be understood by humans. |
| <i>message</i> | A System.String that describes the error. The content of <i>message</i> is intended to be understood by humans. The caller of this constructor is required to ensure that this string has been localized for the current system culture. |

15
16

16 Description

17 This constructor initializes the
18 **System.DuplicateWaitObjectException.ParamName** property of
19 the new instance using *parameterName*, and the
20 **System.DuplicateWaitObjectException.Message** property using
21 *message*. If *message* is **null**, the
22 **System.DuplicateWaitObjectException.Message** property is
23 initialized to the system-supplied message provided by the constructor
24 that takes no arguments.

25
26
27

The **System.DuplicateWaitObjectException.InnerException** property is initialized to **null**.

28