System.Xml.Formatting Enum

```
[ILASM]
.class public sealed serializable Formatting extends
System.Enum

[C#]
public enum Formatting
```

Assembly Info:

- *Name:* System.Xml
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00 00]
- *Version:* 1.0.x.x
- *Attributes:*
  - o CLSCompliantAttribute(true)

Summary

Specifies formatting options for the **System.Xml.XmlTextWriter** class.

Inherits From: System.Enum

Library: XML

Formatting.Indented Field

```
[ILASM]
.field public static literal valuetype
System.Xml.Formatting Indented = 1


[C#]
Indented = 1
```

Summary

Causes child elements to be indented according to the
System.Xml.XmlTextWriter.Indentation and
System.Xml.XmlTextWriter.IndentChar settings. This option
indents element content only; mixed content is not affected.

[*Note:* For the XML 1.0 definitions of these terms, see the W3C
documentation (http://www.w3.org/TR/1998/REC-xml-19980210#sec-
element-content and http://www.w3.org/TR/1998/REC-xml-
19980210#sec-mixed-content).]

Formatting.None Field

```
[ILASM]
.field public static literal valuetype
System.Xml.Formatting None = 0


[C#]
None = 0
```

Summary

No special formatting is applied. This is the default.