

# 1 System.Net.SocketAddress Class

```
2 [ILAsm]  
3 .class public SocketAddress extends System.Object  
  
4 [C#]  
5 public class SocketAddress
```

## 6 Assembly Info:

- 7 • *Name:* System
- 8 • *Public Key:* [00 00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- 9 • *Version:* 2.0.x.x
- 10 • *Attributes:*
  - 11 ○ CLSCompliantAttribute(true)

## 12 Type Attributes:

- 13 • DefaultMemberAttribute("Item") [*Note:* This attribute requires the  
14 RuntimeInfrastructure library.]

## 15 Summary

16 Provides a socket address stored in a `System.Byte` array.

## 17 Inherits From: System.Object

18

19 **Library:** Networking

20

21 **Thread Safety:** All public static members of this type are safe for multithreaded operations.  
22 No instance members are guaranteed to be thread safe.

23

## 24 Description

25 At a minimum, a socket address consists of a member of the  
26 `System.Net.Sockets.AddressFamily` enumeration stored in the first two bytes of the  
27 array.

28

1  
2 **SocketAddress(System.Net.Sockets.AddressF**  
3 **amily) Constructor**

```
4 [ILAsm]  
5 public rtspecialname specialname instance void .ctor(valuetype  
6 System.Net.Sockets.AddressFamily family)  
7 [C#]  
8 public SocketAddress(AddressFamily family)
```

9 **Summary**

10 Constructs and initializes a new instance of the System.Net.SocketAddress class.

11 **Parameters**

Parameter	Description
<i>family</i>	One of the values of the System.Net.Sockets.AddressFamily enumeration.

12  
13 **Description**

14 This method is equivalent to System.Net.SocketAddress.SocketAddress(*family*, 32).

15

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17

# SocketAddress(System.Net.Sockets.AddressFamily, System.Int32) Constructor

```
[ILAsm]  
public rtspecialname specialname instance void .ctor(valuetype  
System.Net.Sockets.AddressFamily family, int32 size)  
  
[C#]  
public SocketAddress(AddressFamily family, int size)
```

## Summary

Constructs and initializes a new instance of the `System.Net.SocketAddress` class.

## Parameters

Parameter	Description
<i>family</i>	One of the values of the <code>System.Net.Sockets.AddressFamily</code> enumeration.
<i>size</i>	A <code>System.Int32</code> containing the number of bytes to allocate for the <code>System.Byte</code> array storing the socket address.

## Description

The minimum value for *size* is 2 bytes.

## Exceptions

Exception	Condition
<code>System.ArgumentOutOfRangeException</code>	<i>size</i> is less than 2.

# 1 SocketAddress.Equals(System.Object)

## 2 Method

```
3 [ILAsm]  
4 .method public hidebysig virtual bool Equals(object comparand)  
5 [C#]  
6 public override bool Equals(object comparand)
```

### 7 Summary

8 Determines whether the current instance and the specified `System.Object` represent the  
9 same socket address.

### 10 Parameters

Parameter	Description
<i>comparand</i>	The <code>System.Object</code> to compare to the current instance.

### 11 Return Value

13 A `System.Boolean` where `true` indicates *comparand* is an instance of the  
14 `System.Net.SocketAddress` class and contains the same data as the current instance;  
15 otherwise `false`.

### 16 Description

17 [Note: This method overrides `System.Object.Equals`.  
18 ]  
19 ]

20

# 1 SocketAddress.GetHashCode() Method

```
2 [ILAsm]  
3 .method public hidebysig virtual int32 GetHashCode()  
4 [C#]  
5 public override int GetHashCode()
```

## 6 Summary

7 Generates a hash code for the current instance.

## 8 Return Value

9 A `System.Int32` containing the hash code for the current instance.

## 10 Description

11 The algorithm used to generate the hash code is unspecified.

12

13 [*Note:* This method overrides `System.Object.GetHashCode`.

14

15 ]

16

# 1 SocketAddress.ToString() Method

```
2 [ILAsm]  
3 .method public hidebysig virtual string ToString()  
4 [C#]  
5 public override string ToString()
```

## 6 Summary

7 Returns a `System.String` representation of the value of the current instance.

## 8 Return Value

9 A `System.String` representation of the current instance.

## 10 Description

11 The returned string contains the string representation of the address family, the length  
12 of the array holding the socket address, and the contents of the array from the third to  
13 the maximum element, output in the following format:

```
14  
15 System.Net.SocketAddress.Family:System.Net.SocketAddress.Size:{array[2],  
16 array[3],..., element[Size- 1]}
```

17  
18 [*Note:* This method overrides `System.Object.ToString`.

19  
20 ]

## 21 Example

22 The following example writes a socket address to the console.

```
23 [C#]  
24  
25 using System;  
26 using System.Net;  
27 using System.Net.Sockets;  
28  
29 public class SocketAddressToString{  
30     public static void Main() {  
31         Console.WriteLine("This is a minimal SocketAddress.");  
32         SocketAddress socketAddress = new  
33             SocketAddress(AddressFamily.InterNetwork);  
34         Console.WriteLine("{0}", socketAddress.ToString());  
35     }  
36 }  
37
```

38 The output is

```
39  
40 This is a minimal SocketAddress.  
41
```



# 1 SocketAddress.Family Property

```
2 [ILAsm]  
3 .property valuetype System.Net.Sockets.AddressFamily Family { public  
4 hidebysig specialname instance valuetype System.Net.Sockets.AddressFamily  
5 get_Family() }  
6 [C#]  
7 public AddressFamily Family { get; }
```

## 8 Summary

9 Gets the address family which specifies the addressing scheme used to resolve an  
10 address.

## 11 Property Value

12 One of the values defined in the `System.Net.Sockets.AddressFamily` enumeration.

## 13 Description

14 This property is read-only.

15

16 This property is set by the `System.Net.SocketAddress` constructors and is stored in the  
17 first two bytes of the socket address array.

18

# 1 SocketAddress.Item Property

```
2 [ILAsm]
3 .property unsigned int8 Item[int32 offset] { public hidebysig specialname
4 instance unsigned int8 get_Item(int32 offset) public hidebysig specialname
5 instance void set_Item(int32 offset, unsigned int8 value) }
6
7 [C#]
8 public byte this[int offset] { get; set; }
```

## 8 Summary

9 Gets or sets the element at the specified index of the `System.Byte` array storing the  
10 socket address.

## 11 Parameters

Parameter	Description
<i>offset</i>	A <code>System.Int32</code> containing the zero-based index of the element to get or set.

## 12 13 Property Value

14 A `System.Byte` containing the element at the specified index.

## 15 Exceptions

Exception	Condition
<b>System.IndexOutOfRangeException</b>	<i>offset</i> is < 0. -or- <i>offset</i> >= <code>System.Net.SocketAddress.Size</code> .

16  
17

# 1 SocketAddress.Size Property

```
2 [ILAsm]  
3 .property int32 Size { public hidebysig specialname instance int32  
4 get_Size() }  
5 [C#]  
6 public int Size { get; }
```

## 7 Summary

8 Gets the length of the socket address.

## 9 Property Value

10 A `System.Int32` containing the length of the `System.Byte` array storing the socket  
11 address.

## 12 Description

13 This property is read-only.

14

15 This property is set by the `System.Net.SocketAddress` constructors.

16