

1 System.Net.Sockets.Socket Class

```
2 [ILAsm]  
3 .class public Socket extends System.Object implements System.IDisposable  
4 [C#]  
5 public class Socket: IDisposable
```

6 Assembly Info:

- 7 • *Name:* System
- 8 • *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00 00]
- 9 • *Version:* 2.0.x.x
- 10 • *Attributes:*
 - 11 ○ CLSCompliantAttribute(true)

12 Implements:

- 13 • **System.IDisposable**

14 Summary

15 Creates a communication endpoint through which an application sends or receives data
16 across a network.

17 Inherits From: System.Object

18

19 **Library:** Networking

20

21 **Thread Safety:** All public static members of this type are safe for multithreaded operations.
22 No instance members are guaranteed to be thread safe.

23

24 Description

25 This class enables a `System.Net.Sockets.Socket` instance to communicate with
26 another socket across a network. The communication can be through connection-
27 oriented and connectionless protocols using either data streams or datagrams (discrete
28 message packets).

29

30 Message-oriented protocols preserve message boundaries and require that for each
31 `System.Net.Sockets.Socket.Send` method call there is one corresponding
32 `System.Net.Sockets.Socket.Receive` method call. For stream-oriented protocols, data
33 is transmitted without regards to message boundaries. In this case, for example,
34 multiple `System.Net.Sockets.Socket.Receive` method calls might be necessary to
35 retrieve all the data from one `System.Net.Sockets.Socket.Send` method call. The
36 protocol is set in the `Socket` class constructor.

37

38 A `System.Net.Sockets.Socket` instance has a local and a remote endpoint associated
39 with it. The local endpoint contains the connection information for the current socket

1 instance. The remote endpoint contains the connection information for the socket that
2 the current instance communicates with. The endpoints are required to be an instance of
3 a type derived from the `System.Net.EndPoint` class. For the Transmission Control
4 Protocol (TCP) and User Datagram Protocol (UDP) protocols, an endpoint includes the
5 address family, an Internet Protocol (IP) address, and a port number. For connection-
6 oriented protocols (for example, TCP), the remote endpoint does not have to be
7 specified when transferring data. For connectionless protocols (for example, UDP), the
8 remote endpoint is required to be specified.

9
10 Methods are provided for both synchronous and asynchronous operations. A
11 synchronous method can operate in blocking mode, in which it waits (blocks) until the
12 operation is complete before returning, or in non-blocking mode, where it returns
13 immediately, possibly before the operation has completed. The blocking mode is set
14 through the `System.Net.Sockets.Socket.Blocking` property.

15
16 An asynchronous method returns immediately and, by convention, relies on a delegate
17 to complete the operation. Asynchronous methods have names which correspond to
18 their synchronous counterparts prefixed with either 'Begin' or 'End'. For example, the
19 synchronous `System.Net.Sockets.Socket.Accept` method has asynchronous
20 counterpart methods named `System.Net.Sockets.Socket.BeginAccept` and
21 `System.Net.Sockets.Socket.EndAccept`. The example for the
22 `System.Net.Sockets.Socket.BeginAccept` method shows the basic steps for using an
23 asynchronous operation. A complete working example follows this discussion.

24
25 Connection-oriented protocols commonly use the client/server model. In this model, one
26 of the sockets is set up as a server, and one or more sockets are set up as clients. A
27 general procedure demonstrating the synchronous communication process for this
28 model is as follows.

29
30 On the server-side:

- 31 1. Create a socket to listen for incoming connection requests.
- 32 2. Set the local endpoint using the `System.Net.Sockets.Socket.Bind` method.
- 33 3. Put the socket in the listening state using the `System.Net.Sockets.Socket.Listen`
34 method.
- 35 4. At this point incoming connection requests from a client are placed in a queue.
- 36 5. Use the `System.Net.Sockets.Socket.Accept` method to create a server socket for a
37 connection request issued by a client-side socket. This sets the remote endpoint.
- 38 6. Use the `System.Net.Sockets.Socket.Send` and
39 `System.Net.Sockets.Socket.Receive` methods to communicate with the client
40 socket.
- 41 7. When communication is finished, terminate the connection using the
42 `System.Net.Sockets.Socket.Shutdown` method.
- 43 8. Release the resources allocated by the server socket using the
44 `System.Net.Sockets.Socket.Close` method.
- 45 9. Release the resources allocated by the listener socket using the
46 `System.Net.Sockets.Socket.Close` method.

47 On the client-side:

- 48 1. Create the client socket.

- 1 2. Connect to the server socket using the `System.Net.Sockets.Socket.Connect`
- 2 method. This sets both the local and remote endpoints for the client socket.
- 3 3. Use the `System.Net.Sockets.Socket.Send` and
- 4 `System.Net.Sockets.Socket.Receive` methods to communicate with the server
- 5 socket.
- 6 4. When communication is finished, terminate the connection using the
- 7 `System.Net.Sockets.Socket.Shutdown` method.
- 8 5. Release the resources allocated by the client socket using the
- 9 `System.Net.Sockets.Socket.Close` method.

10 The shutdown step in the previous procedure is not necessary but ensures that any pending
11 data is not lost. If the `System.Net.Sockets.Socket.Shutdown` method is not called, the
12 `System.Net.Sockets.Socket.Close` method shuts down the connection either gracefully or
13 by force. A graceful closure attempts to transfer all pending data before the connection is
14 terminated. Use the `System.Net.Sockets.SocketOptionName.Linger` socket option to
15 specify a graceful closure for a socket.

16
17 [*Note:* This implementation is based on the UNIX sockets implementation in the Berkeley
18 Software Distribution (BSD, release 4.3) from the University of California at Berkeley.

19
20]

21 **Example**

22 The following examples provide a client/server application that demonstrates the use of
23 asynchronous communication between sockets. Run the client and server on different
24 consoles.

25
26 The following code is for the server application. Start this application before the client
27 application.

```
28       [C#]
29
30 using System;
31 using System.Threading;
32 using System.Text;
33 using System.Net;
34 using System.Net.Sockets;
35
36 public class Server
37 {
38     // used to pass state information to delegate
39     internal class StateObject
40     {
41         internal byte[] sBuffer;
42         internal Socket sSocket;
43         internal StateObject(int size, Socket sock) {
44             sBuffer = new byte[size];
45             sSocket = sock;
46         }
47     }
48     static void Main()
```

```

1  {
2      IPAddress ipAddress =
3          Dns.Resolve( Dns.GetHostName() ).AddressList[0];
4
5      IPEndPoint ipEndpoint =
6          new IPEndPoint(ipAddress, 1800);
7
8      Socket listenSocket =
9          new Socket(AddressFamily.InterNetwork,
10                 SocketType.Stream,
11                 ProtocolType.Tcp);
12
13     listenSocket.Bind(ipEndpoint);
14     listenSocket.Listen(1);
15     IAsyncResult asyncAccept = listenSocket.BeginAccept(
16         new AsyncCallback(Server.acceptCallback),
17         listenSocket );
18
19     // could call listenSocket.EndAccept(asyncAccept) here
20     // instead of in the callback method, but since
21     // EndAccept blocks, the behavior would be similar to
22     // calling the synchronous Accept method
23
24     Console.WriteLine("Connection in progress.");
25     if( writeDot(asyncAccept) == true )
26     {
27         // allow time for callbacks to
28         // finish before the program ends
29         Thread.Sleep(3000);
30     }
31 }
32
33 public static void
34 acceptCallback(IAsyncResult asyncAccept) {
35     Socket listenSocket = (Socket)asyncAccept.AsyncState;
36     Socket serverSocket =
37         listenSocket.EndAccept(asyncAccept);
38
39     // arriving here means the operation completed
40     // (asyncAccept.IsCompleted = true) but not
41     // necessarily successfully
42     if( serverSocket.Connected == false )
43     {
44         Console.WriteLine( ".server is not connected." );
45         return;
46     }
47     else Console.WriteLine( ".server is connected." );
48
49     listenSocket.Close();
50
51     StateObject stateObject =
52         new StateObject(16, serverSocket);
53
54     // this call passes the StateObject because it
55     // needs to pass the buffer as well as the socket
56     IAsyncResult asyncReceive =
57         serverSocket.BeginReceive(

```

```

1         stateObject.sBuffer,
2         0,
3         stateObject.sBuffer.Length,
4         SocketFlags.None,
5         new AsyncCallback(receiveCallback),
6         stateObject);
7
8     Console.Write("Receiving data.");
9     writeDot(asyncReceive);
10 }
11
12 public static void
13 receiveCallback(IAsyncResult asyncReceive) {
14     StateObject stateObject =
15         (StateObject)asyncReceive.AsyncState;
16     int bytesReceived =
17         stateObject.sSocket.EndReceive(asyncReceive);
18
19     Console.WriteLine(
20         ".{0} bytes received: {1}",
21         bytesReceived.ToString(),
22         Encoding.ASCII.GetString(stateObject.sBuffer) );
23
24     byte[] sendBuffer =
25         Encoding.ASCII.GetBytes("Goodbye");
26     IAsyncResult asyncSend =
27         stateObject.sSocket.BeginSend(
28             sendBuffer,
29             0,
30             sendBuffer.Length,
31             SocketFlags.None,
32             new AsyncCallback(sendCallback),
33             stateObject.sSocket);
34
35     Console.Write("Sending response.");
36     writeDot(asyncSend);
37 }
38
39 public static void sendCallback(IAsyncResult asyncSend) {
40     Socket serverSocket = (Socket)asyncSend.AsyncState;
41     int bytesSent = serverSocket.EndSend(asyncSend);
42     Console.WriteLine(
43         ".{0} bytes sent.{1}{1}Shutting down.",
44         bytesSent.ToString(),
45         Environment.NewLine );
46
47     serverSocket.Shutdown(SocketShutdown.Both);
48     serverSocket.Close();
49 }
50
51 // times out after 20 seconds but operation continues
52 internal static bool writeDot(IAsyncResult ar)
53 {
54     int i = 0;
55     while( ar.IsCompleted == false )
56     {
57         if( i++ > 40 )

```

```

1      {
2          Console.WriteLine("Timed out.");
3          return false;
4      }
5      Console.Write(".");
6      Thread.Sleep(500);
7      }
8      return true;
9      }
10     }

```

12 The following code is for the client application. When starting the application, supply the
13 hostname of the console running the server application as an input parameter (for example,
14 `ProgramName hostname`).

15 [C#]

```

17 using System;
18 using System.Threading;
19 using System.Text;
20 using System.Net;
21 using System.Net.Sockets;
22
23 public class Client {
24
25     // used to pass state information to delegate
26     class StateObject
27     {
28         internal byte[] sBuffer;
29         internal Socket sSocket;
30         internal StateObject(int size, Socket sock) {
31             sBuffer = new byte[size];
32             sSocket = sock;
33         }
34     }
35
36     static void Main(string[] argHostName)
37     {
38         IPAddress ipAddress =
39             Dns.Resolve( argHostName[0] ).AddressList[0];
40
41         IPEndPoint ipEndpoint =
42             new IPEndPoint(ipAddress, 1800);
43
44         Socket clientSocket = new Socket(
45             AddressFamily.InterNetwork,
46             SocketType.Stream,
47             ProtocolType.Tcp);
48
49         IAsyncResult asyncConnect = clientSocket.BeginConnect(
50             ipEndpoint,
51             new AsyncCallback(connectCallback),
52             clientSocket );
53
54         Console.Write("Connection in progress.");
55         if( writeDot(asyncConnect) == true )

```

```

1      {
2          // allow time for callbacks to
3          // finish before the program ends
4          Thread.Sleep(3000);
5      }
6  }
7
8  public static void
9  connectCallback(IAsyncResult asyncConnect) {
10     Socket clientSocket =
11         (Socket)asyncConnect.AsyncState;
12     clientSocket.EndConnect(asyncConnect);
13     // arriving here means the operation completed
14     // (asyncConnect.IsCompleted = true) but not
15     // necessarily successfully
16     if( clientSocket.Connected == false )
17     {
18         Console.WriteLine( ".client is not connected." );
19         return;
20     }
21     else Console.WriteLine( ".client is connected." );
22
23     byte[] sendBuffer = Encoding.ASCII.GetBytes("Hello");
24     IAsyncResult asyncSend = clientSocket.BeginSend(
25         sendBuffer,
26         0,
27         sendBuffer.Length,
28         SocketFlags.None,
29         new AsyncCallback(sendCallback),
30         clientSocket);
31
32     Console.Write("Sending data.");
33     writeDot(asyncSend);
34 }
35
36 public static void sendCallback(IAsyncResult asyncSend)
37 {
38     Socket clientSocket = (Socket)asyncSend.AsyncState;
39     int bytesSent = clientSocket.EndSend(asyncSend);
40     Console.WriteLine(
41         ".{0} bytes sent.",
42         bytesSent.ToString() );
43
44     StateObject stateObject =
45         new StateObject(16, clientSocket);
46
47     // this call passes the StateObject because it
48     // needs to pass the buffer as well as the socket
49     IAsyncResult asyncReceive =
50         clientSocket.BeginReceive(
51             stateObject.sBuffer,
52             0,
53             stateObject.sBuffer.Length,
54             SocketFlags.None,
55             new AsyncCallback(receiveCallback),
56             stateObject);
57

```

```

1     Console.WriteLine("Receiving response.");
2     writeDot(asyncReceive);
3 }
4
5 public static void
6     receiveCallback(IAsyncResult asyncReceive) {
7     StateObject stateObject =
8         (StateObject)asyncReceive.AsyncState;
9
10    int bytesReceived =
11        stateObject.sSocket.EndReceive(asyncReceive);
12
13    Console.WriteLine(
14        ".{0} bytes received: {1}{2}{2}Shutting down.",
15        bytesReceived.ToString(),
16        Encoding.ASCII.GetString(stateObject.sBuffer),
17        Environment.NewLine );
18
19    stateObject.sSocket.Shutdown(SocketShutdown.Both);
20    stateObject.sSocket.Close();
21 }
22
23 // times out after 2 seconds but operation continues
24 internal static bool writeDot(IAsyncResult ar)
25 {
26     int i = 0;
27     while( ar.IsCompleted == false )
28     {
29         if( i++ > 20 )
30         {
31             Console.WriteLine("Timed out.");
32             return false;
33         }
34         Console.Write(".");
35         Thread.Sleep(100);
36     }
37     return true;
38 }
39 }

```

40
41 The output of the server application is

42
43 Connection in progress.....server is connected.

44
45
46 Receiving data.....5 bytes received: Hello

47
48
49 Sending response....7 bytes sent.

50
51
52 Shutting down.

53
54

```
1 -----  
2  
3  
4 The output of the client application is  
5  
6 Connection in progress.....client is connected.  
7  
8  
9 Sending data.....5 bytes sent.  
10  
11  
12 Receiving response.....7 bytes received: Goodbye  
13  
14  
15 Shutting down.  
16  
17
```

Socket(System.Net.Sockets.AddressFamily, System.Net.Sockets.SocketType, System.Net.Sockets.ProtocolType) Constructor

```
[ILAsm]
public rtspecialname specialname instance void .ctor(valuetype
System.Net.Sockets.AddressFamily addressFamily, valuetype
System.Net.Sockets.SocketType socketType, valuetype
System.Net.Sockets.ProtocolType protocolType)

[C#]
public Socket(AddressFamily addressFamily, SocketType socketType,
ProtocolType protocolType)
```

Summary

Constructs and initializes a new instance of the `System.Net.Sockets.Socket` class.

Parameters

| Parameter | Description |
|----------------------|---|
| <i>addressFamily</i> | One of the values defined in the <code>System.Net.Sockets.AddressFamily</code> enumeration. |
| <i>socketType</i> | One of the values defined in the <code>System.Net.Sockets.SocketType</code> enumeration. |
| <i>protocolType</i> | One of the values defined in the <code>System.Net.Sockets.ProtocolType</code> enumeration. |

Description

The *addressFamily* parameter specifies the addressing scheme used by the current instance, the *socketType* parameter specifies the socket type of the current instance, and the *protocolType* parameter specifies the protocol used by the current instance. The three parameters are not independent. Some address families restrict which protocols are used, and often the socket type is determined by the protocol. When the specified values are not a valid combination, a `System.Net.Sockets.SocketException` exception is thrown.

Using the `Unknown` member of either the `System.Net.Sockets.AddressFamily` or `System.Net.Sockets.ProtocolType` enumeration, results in a `System.Net.Sockets.SocketException` exception being thrown.

1 Exceptions

| Exception | Condition |
|---|--|
| System.Net.Sockets.SocketException | The combination of <i>addressFamily</i> , <i>socketType</i> , and <i>protocolType</i> is invalid. -or- An error occurred while creating the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |

2

3

1 Socket.Accept() Method

```
2 [ILAsm]  
3 .method public hidebysig instance class System.Net.Sockets.Socket Accept()  
4 [C#]  
5 public Socket Accept()
```

6 Summary

7 Creates and initializes a new `System.Net.Sockets.Socket` instance and connects it to
8 an incoming connection request.

9 Return Value

10 A new connected `System.Net.Sockets.Socket` instance.

11 Description

12 This method is used only on the server-side of connection-oriented protocols. It extracts
13 the first connection request from the queue of pending requests, creates a new
14 `System.Net.Sockets.Socket` instance, and connects this instance to the socket
15 associated with the request.

16
17 The `System.Net.Sockets.Socket.Blocking` property of the socket determines the
18 behavior of this method when there are no pending connection requests. When `false`,
19 this method will throw a `System.Net.Sockets.SocketException`. When `true`, this
20 method blocks.

21
22 The following properties of the new `System.Net.Sockets.Socket` instance returned by
23 this method have values identical to the corresponding properties of the current
24 instance:

- 25 • `System.Net.Sockets.Socket.AddressFamily`
- 26 • `System.Net.Sockets.Socket.Blocking`
- 27 • `System.Net.Sockets.Socket.LocalEndPoint`
- 28 • `System.Net.Sockets.Socket.ProtocolType`
- 29 • `System.Net.Sockets.Socket.SocketType`

30 The `System.Net.Sockets.Socket.RemoteEndPoint` property of the new instance is set to
31 the local endpoint of the first request in the input queue. The
32 `System.Net.Sockets.Socket.Connected` property is set to `true`.

33 Exceptions

| Exception | Condition |
|---|--|
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | <p>An error occurred while accessing the listening socket or while creating the new socket.</p> <p>-or-</p> <p>The <code>System.Net.Sockets.Socket.Blocking</code> property is set to <code>false</code>.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2

Socket.BeginAccept(System.AsyncCallback, System.Object) Method

```
[ILAsm]  
.method public hidebysig instance class System.IAsyncResult  
BeginAccept(class System.AsyncCallback callback, object state)  
  
[C#]  
public IAsyncResult BeginAccept(AsyncCallback callback, object state)
```

Summary

Begins an asynchronous operation to accept an incoming connection request.

Parameters

| Parameter | Description |
|-----------------|---|
| <i>callback</i> | A System.AsyncCallback delegate, or null. |
| <i>state</i> | An application-defined object, or null. |

Return Value

A System.IAsyncResult instance that contains information about the asynchronous operation.

Description

To retrieve the results of the operation and release resources allocated by the System.Net.Sockets.Socket.BeginAccept method, call the System.Net.Sockets.Socket.EndAccept method, and specify the System.IAsyncResult object returned by this method.

[*Note:* The System.Net.Sockets.Socket.EndAccept method should be called exactly once for each call to the System.Net.Sockets.Socket.BeginAccept method.]

If the *callback* parameter is not null, the method referenced by *callback* is invoked when the asynchronous operation completes. The System.IAsyncResult object returned by this method is passed as the argument to the method referenced by *callback*. The method referenced by *callback* can retrieve the results of the operation by calling the System.Net.Sockets.Socket.EndAccept method.

The *state* parameter can be any object that the caller wishes to have available for the duration of the asynchronous operation. This object is available via the System.IAsyncResult.AsyncState property of the object returned by this method.

1
 2 To determine the connection status, check the `System.Net.Sockets.Socket.Connected`
 3 property, or use either the `System.Net.Sockets.Socket.Poll` or
 4 `System.Net.Sockets.Socket.Select` method.
 5
 6 [Note: For more information, see `System.Net.Sockets.Socket.Accept`, the
 7 synchronous version of this method.
 8
 9]

10 **Exceptions**

| Exception | Condition |
|---|--|
| System.Net.Sockets.SocketException | An error occurred while accepting the connection. [Note: For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

11
 12 **Example**

13 The following excerpt from the `System.Net.Sockets.Socket` class overview example
 14 outlines an asynchronous accept operation.

```
15 [C#]
16
17 public class Server
18 {
19     static void Main()
20     {
21         .
22         .
23         .
24         listenSocket.BeginAccept(
25             new AsyncCallback(Server.acceptCallback),
26             listenSocket);
27         .
28         .
29         .
30         // EndAccept can be called here
31         .
32         .
33         .
34     }
35
36     public static void
```

```
1     acceptCallback(IAsyncResult asyncAccept)
2     {
3         Socket listenSocket =
4             (Socket)asyncAccept.AsyncState;
5
6         Socket serverSocket =
7             listenSocket.EndAccept(asyncAccept);
8
9         serverSocket.BeginReceive(...);
10    .
11    .
12    .
13    }
14 }
15
```

Socket.BeginConnect(System.Net.EndPoint, System.AsyncCallback, System.Object)

Method

```
[ILAsm]  
.method public hidebysig instance class System.IAsyncResult  
BeginConnect(class System.Net.EndPoint remoteEP, class  
System.AsyncCallback callback, object state)  
  
[C#]  
public IAsyncResult BeginConnect(EndPoint remoteEP, AsyncCallback  
callback, object state)
```

Summary

Begins an asynchronous operation to associate the current instance with a remote endpoint.

Parameters

| Parameter | Description |
|-----------------|--|
| <i>remoteEP</i> | The <i>System.Net.EndPoint</i> associated with the socket to connect to. |
| <i>callback</i> | A <i>System.AsyncCallback</i> delegate, or null. |
| <i>state</i> | An application-defined object, or null. |

Return Value

A *System.IAsyncResult* instance that contains information about the asynchronous operation.

Description

To release resources allocated by the *System.Net.Sockets.Socket.BeginConnect* method, call the *System.Net.Sockets.Socket.EndConnect* method, and specify the *System.IAsyncResult* object returned by this method.

[*Note:* The *System.Net.Sockets.Socket.EndConnect* method should be called exactly once for each call to the *System.Net.Sockets.Socket.BeginConnect* method.]

If the *callback* parameter is not null, the method referenced by *callback* is invoked when the asynchronous operation completes. The *System.IAsyncResult* object

1 returned by this method is passed as the argument to the method referenced by
2 *callback*. The method referenced by *callback* can retrieve the results of the operation by
3 calling the `System.Net.Sockets.Socket.EndConnect` method.

4
5 The *state* parameter can be any object that the caller wishes to have available for the
6 duration of the asynchronous operation. This object is available via the
7 `System.IAsyncResult.AsyncState` property of the object returned by this method.

8
9 To determine the connection status, check the `System.Net.Sockets.Socket.Connected`
10 property, or use either the `System.Net.Sockets.Socket.Poll` or
11 `System.Net.Sockets.Socket.Select` method.

12
13 [*Note:* For more information, see `System.Net.Sockets.Socket.Connect`, the
14 synchronous version of this method.

15
16]

17 Exceptions

| Exception | Condition |
|---|---|
| <code>System.ArgumentNullException</code> | <i>remoteEP</i> is null. |
| <code>System.Net.Sockets.SocketException</code> | An error occurred while making the connection. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| <code>System.ObjectDisposedException</code> | The current instance has been disposed. |
| <code>System.Security.SecurityException</code> | A caller higher in the call stack does not have permission for the requested operation. |

18 19 Example

20 For an outline of an asynchronous operation, see the
21 `System.Net.Sockets.Socket.BeginAccept` method. For the complete example, which
22 uses the `System.Net.Sockets.Socket.BeginConnect` method, see the
23 `System.Net.Sockets.Socket` class overview.

24 Permissions

| Permission | Description |
|------------|-------------|
|------------|-------------|

| | |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to make a connection to the endpoint defined by <i>remoteEP</i> . [Note: See <code>System.Net.NetworkAccess.Connect</code> .] |
|------------------------------------|---|

1

2

1 **Socket.BeginReceive(System.Byte[],**
2 **System.Int32, System.Int32,**
3 **System.Net.Sockets.SocketFlags,**
4 **System.AsyncCallback, System.Object)**
5 **Method**

```
6 [ILAsm]  
7 .method public hidebysig instance class System.IAsyncResult  
8 BeginReceive(class System.Byte[] buffer, int32 offset, int32 size,  
9 valuetype System.Net.Sockets.SocketFlags socketFlags, class  
10 System.AsyncCallback callback, object state)  
  
11 [C#]  
12 public IAsyncResult BeginReceive(byte[] buffer, int offset, int size,  
13 SocketFlags socketFlags, AsyncCallback callback, object state)
```

14 **Summary**

15 Begins an asynchronous operation to receive data from a socket.

16 **Parameters**

| Parameter | Description |
|--------------------|---|
| <i>buffer</i> | A System.Byte array to store data received from the socket. |
| <i>offset</i> | A System.Int32 containing the zero-based position in <i>buffer</i> to begin storing the received data. |
| <i>size</i> | A System.Int32 containing the number of bytes to receive. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.OutOfBand, or System.Net.Sockets.SocketFlags.Peek. |
| <i>callback</i> | A System.AsyncCallback delegate, or null. |
| <i>state</i> | An application-defined object, or null. |

17
18 **Return Value**

1 A `System.IAsyncResult` instance that contains information about the asynchronous
2 operation.

3 Description

4 To retrieve the results of the operation and release resources allocated by the
5 `System.Net.Sockets.Socket.BeginReceive` method, call the
6 `System.Net.Sockets.Socket.EndReceive` method, and specify the
7 `System.IAsyncResult` object returned by this method.

8
9 *[Note: The `System.Net.Sockets.Socket.EndReceive` method should be called exactly
10 once for each call to the `System.Net.Sockets.Socket.BeginReceive` method.]*
11

12
13
14 If the *callback* parameter is not `null`, the method referenced by *callback* is invoked
15 when the asynchronous operation completes. The `System.IAsyncResult` object
16 returned by this method is passed as the argument to the method referenced by
17 *callback*. The method referenced by *callback* can retrieve the results of the operation by
18 calling the `System.Net.Sockets.Socket.EndReceive` method.
19

20 The *state* parameter can be any object that the caller wishes to have available for the
21 duration of the asynchronous operation. This object is available via the
22 `System.IAsyncResult.AsyncState` property of the object returned by this method.
23

24 *[Note: For more information, see `System.Net.Sockets.Socket.Receive`, the
25 synchronous version of this method.]*
26

27]

28 Exceptions

| Exception | Condition |
|---|--|
| <code>System.ArgumentNullException</code> | <i>buffer</i> is <code>null</code> . |
| <code>System.ArgumentOutOfRangeException</code> | <i>offset</i> < 0. -or- <i>offset</i> > <i>buffer.Length</i> . -or- <i>size</i> < 0. -or- |

| | |
|---|---|
| | <i>size > buffer.Length - offset.</i> |
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Example**

3 For an outline of an asynchronous operation, see the
4 `System.Net.Sockets.Socket.BeginAccept` method. For the complete example, which
5 uses the `System.Net.Sockets.Socket.BeginReceive` method, see the
6 `System.Net.Sockets.Socket` class overview.

7

1 **Socket.BeginReceiveFrom(System.Byte[],**
2 **System.Int32, System.Int32,**
3 **System.Net.Sockets.SocketFlags,**
4 **System.Net.EndPoint&**
5 **System.AsyncCallback, System.Object)**
6 **Method**

```
7 [ILAsm]  
8 .method public hidebysig instance class System.IAsyncResult  
9 BeginReceiveFrom(class System.Byte[] buffer, int32 offset, int32 size,  
10 valuetype System.Net.Sockets.SocketFlags socketFlags, class  
11 System.Net.EndPoint& remoteEP, class System.AsyncCallback callback, object  
12 state)  
  
13 [C#]  
14 public IAsyncResult BeginReceiveFrom(byte[] buffer, int offset, int size,  
15 SocketFlags socketFlags, ref EndPoint remoteEP, AsyncCallback callback,  
16 object state)
```

17 **Summary**

18 Begins an asynchronous operation to receive data from a socket and, for connectionless
19 protocols, store the endpoint associated with the socket that sent the data.

20 **Parameters**

| Parameter | Description |
|--------------------|---|
| <i>buffer</i> | A System.Byte array to store data received from the socket. |
| <i>offset</i> | A System.Int32 containing the zero-based position in <i>buffer</i> to begin storing the received data. |
| <i>size</i> | A System.Int32 containing the number of bytes to receive. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.OutOfBand, or System.Net.Sockets.SocketFlags.Peek. |
| <i>remoteEP</i> | An instance of a class derived from the System.Net.EndPoint class, which contains the endpoint associated with the socket that sent the data. |

| | |
|-----------------|--|
| <i>callback</i> | A <code>System.AsyncCallback</code> delegate, or null. |
| <i>state</i> | An application-defined object, or null. |

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30

Return Value

A `System.IAsyncResult` instance that contains information about the asynchronous operation.

Description

To retrieve the results of the operation and release resources allocated by the `System.Net.Sockets.Socket.BeginReceiveFrom` method, call the `System.Net.Sockets.Socket.EndReceiveFrom` method, and specify the `System.IAsyncResult` object returned by this method.

[*Note:* The `System.Net.Sockets.Socket.EndReceiveFrom` method should be called exactly once for each call to the `System.Net.Sockets.Socket.BeginReceiveFrom` method.]

If the *callback* parameter is not null, the method referenced by *callback* is invoked when the asynchronous operation completes. The `System.IAsyncResult` object returned by this method is passed as the argument to the method referenced by *callback*. The method referenced by *callback* can retrieve the results of the operation by calling the `System.Net.Sockets.Socket.EndReceiveFrom` method.

The *state* parameter can be any object that the caller wishes to have available for the duration of the asynchronous operation. This object is available via the `System.IAsyncResult.AsyncState` property of the object returned by this method.

[*Note:* For more information, see `System.Net.Sockets.Socket.ReceiveFrom`, the synchronous version of this method.

]

Exceptions

| Exception | Condition |
|-------------------------------------|--|
| System.ArgumentNullException | <i>buffer</i> is null. -or- <i>remoteEP</i> is null. |

| | |
|---|---|
| System.ArgumentOutOfRangeException | <p><i>offset</i> < 0.</p> <p>-or-</p> <p><i>offset</i> > <i>buffer.Length</i>.</p> <p>-or-</p> <p><i>size</i> < 0.</p> <p>-or-</p> <p><i>size</i> > <i>buffer.Length</i> - <i>offset</i>.</p> |
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.ObjectDisposedException | The current instance has been disposed. |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |

1

2 **Example**

3 For an outline of an asynchronous operation, see the
 4 `System.Net.Sockets.Socket.BeginAccept` method. For the complete example, see
 5 `System.Net.Sockets.Socket`.

6 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to accept a connection on the |

| | |
|--|--|
| | <p>endpoint defined by the <code>System.Net.Sockets.Socket.LocalEndPoint</code> property of the current instance. See <code>System.Net.NetworkAccess.Accept</code>.</p> <p>Requires permission to make a connection to the endpoint defined by <i>remoteEP</i>. See <code>System.Net.NetworkAccess.Connect</code>.</p> |
|--|--|

1

2

1 Socket.BeginSend(System.Byte[], 2 System.Int32, System.Int32, 3 System.Net.Sockets.SocketFlags, 4 System.AsyncCallback, System.Object) 5 Method

```
6 [ILAsm]  
7 .method public hidebysig instance class System.IAsyncResult  
8 BeginSend(class System.Byte[] buffer, int32 offset, int32 size, valuetype  
9 System.Net.Sockets.SocketFlags socketFlags, class System.AsyncCallback  
10 callback, object state)  
  
11 [C#]  
12 public IAsyncResult BeginSend(byte[] buffer, int offset, int size,  
13 SocketFlags socketFlags, AsyncCallback callback, object state)
```

14 Summary

15 Begins an asynchronous operation to send data to a connected socket.

16 Parameters

| Parameter | Description |
|--------------------|--|
| <i>buffer</i> | A System.Byte array storing data to send to the socket. |
| <i>offset</i> | A System.Int32 containing the zero-based position in <i>buffer</i> containing the starting location of the data to send. |
| <i>size</i> | A System.Int32 containing the number of bytes to send. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.DontRoute, or System.Net.Sockets.SocketFlags.OutOfBand. |
| <i>callback</i> | A System.AsyncCallback delegate, or null. |
| <i>state</i> | An application-defined object, or null. |

17 18 Return Value

1 A `System.IAsyncResult` instance that contains information about the asynchronous
2 operation.

3 **Description**

4 To retrieve the results of the operation and release resources allocated by the
5 `System.Net.Sockets.Socket.BeginSend` method, call the
6 `System.Net.Sockets.Socket.EndSend` method, and specify the `System.IAsyncResult`
7 object returned by this method.

8
9 [*Note:* The `System.Net.Sockets.Socket.EndSend` method should be called exactly once
10 for each call to the `System.Net.Sockets.Socket.BeginSend` method.]

11
12
13
14 If the *callback* parameter is not `null`, the method referenced by *callback* is invoked
15 when the asynchronous operation completes. The `System.IAsyncResult` object
16 returned by this method is passed as the argument to the method referenced by
17 *callback*. The method referenced by *callback* can retrieve the results of the operation by
18 calling the `System.Net.Sockets.Socket.EndSend` method.

19
20 The *state* parameter can be any object that the caller wishes to have available for the
21 duration of the asynchronous operation. This object is available via the
22 `System.IAsyncResult.AsyncState` property of the object returned by this method.

23
24 [*Note:* For more information, see `System.Net.Sockets.Socket.Send`, the synchronous
25 version of this method.

26
27]

28 **Exceptions**

| Exception | Condition |
|---|--|
| System.ArgumentNullException | <i>buffer</i> is <code>null</code> . |
| System.ArgumentOutOfRangeException | <i>offset</i> < 0. |
| | -or- |
| | <i>offset</i> > <i>buffer.Length</i> . |
| | -or- |
| | <i>size</i> < 0. |
| | -or- |

| | |
|---|---|
| | <i>size > buffer.Length - offset.</i> |
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Example**

3 For an outline of an asynchronous operation, see the
4 `System.Net.Sockets.Socket.BeginAccept` method. For the complete example, which
5 uses the `System.Net.Sockets.Socket.BeginSend` method, see the
6 `System.Net.Sockets.Socket` class overview.

7

1 Socket.BeginSendTo(System.Byte[], 2 System.Int32, System.Int32, 3 System.Net.Sockets.SocketFlags, 4 System.Net.EndPoint, System.AsyncCallback, 5 System.Object) Method

```
6 [ILAsm]  
7 .method public hidebysig instance class System.IAsyncResult  
8 BeginSendTo(class System.Byte[] buffer, int32 offset, int32 size,  
9 valuetype System.Net.Sockets.SocketFlags socketFlags, class  
10 System.Net.EndPoint remoteEP, class System.AsyncCallback callback, object  
11 state)  
  
12 [C#]  
13 public IAsyncResult BeginSendTo(byte[] buffer, int offset, int size,  
14 SocketFlags socketFlags, EndPoint remoteEP, AsyncCallback callback, object  
15 state)
```

16 Summary

17 Begins an asynchronous operation to send data to the socket associated with the
18 specified endpoint.

19 Parameters

| Parameter | Description |
|--------------------|--|
| <i>buffer</i> | A System.Byte array storing data to send to the socket. |
| <i>offset</i> | A System.Int32 containing the zero-based position in <i>buffer</i> to begin sending data. |
| <i>size</i> | A System.Int32 containing the number of bytes to send. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.DontRoute, OR System.Net.Sockets.SocketFlags.OutOfBand. |
| <i>remoteEP</i> | The System.Net.EndPoint associated with the socket to receive the data. |
| <i>callback</i> | A System.AsyncCallback delegate, or null. |

| | |
|--------------|---|
| <i>state</i> | An application-defined object, or null. |
|--------------|---|

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29

Return Value

A `System.IAsyncResult` instance that contains information about the asynchronous operation.

Description

To retrieve the results of the operation and release resources allocated by the `System.Net.Sockets.Socket.BeginSendTo` method, call the `System.Net.Sockets.Socket.EndSendTo` method, and specify the `System.IAsyncResult` object returned by this method.

[*Note:* The `System.Net.Sockets.Socket.EndSendTo` method should be called exactly once for each call to the `System.Net.Sockets.Socket.BeginSendTo` method.]

If the *callback* parameter is not null, the method referenced by *callback* is invoked when the asynchronous operation completes. The `System.IAsyncResult` object returned by this method is passed as the argument to the method referenced by *callback*. The method referenced by *callback* can retrieve the results of the operation by calling the `System.Net.Sockets.Socket.EndSendTo` method.

The *state* parameter can be any object that the caller wishes to have available for the duration of the asynchronous operation. This object is available via the `System.IAsyncResult.AsyncState` property of the object returned by this method.

[*Note:* For more information, see `System.Net.Sockets.Socket.SendTo`, the synchronous version of this method.

]

Exceptions

| Exception | Condition |
|---|--|
| System.ArgumentNullException | <i>buffer</i> is null. -or- <i>remoteEP</i> is null. |
| System.ArgumentOutOfRangeException | <i>offset</i> < 0. -or- |

| | |
|---|---|
| | <p><i>offset</i> > <i>buffer.Length</i>.</p> <p>-or-</p> <p><i>size</i> < 0.</p> <p>-or-</p> <p><i>size</i> > <i>buffer.Length</i> - <i>offset</i>.</p> |
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.ObjectDisposedException | The current instance has been disposed. |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |

1

2 **Example**

3 For an outline of an asynchronous operation, see the
 4 `System.Net.Sockets.Socket.BeginAccept` method. For the complete example, see the
 5 `System.Net.Sockets.Socket` class overview.

6 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to make a connection to the endpoint defined by <i>remoteEP</i> . See <code>System.Net.NetworkAccess.Connect</code> . |

7

8

1 Socket.Bind(System.Net.EndPoint) Method

```
2 [ILAsm]  
3 .method public hidebysig instance void Bind(class System.Net.EndPoint  
4 localEP)  
5 [C#]  
6 public void Bind(EndPoint localEP)
```

7 Summary

8 Associates the current instance with a local endpoint.

9 Parameters

| Parameter | Description |
|----------------|--|
| <i>localEP</i> | The local <code>System.Net.EndPoint</code> to be associated with the socket. |

10

11 Description

12 This method sets the `System.Net.Sockets.Socket.LocalEndPoint` property of the
13 current instance to *localEP*.

14

15 [Note: For connection-oriented protocols, this method is generally used only on the
16 server-side and is required to be called before the first call to the
17 `System.Net.Sockets.Socket.Listen` method. On the client-side, binding is usually
18 performed implicitly by the `System.Net.Sockets.Socket.Connect` method.

19

20 For connectionless protocols, the
21 `System.Net.Sockets.Socket.ConnectSystem.Net.Sockets.Socket.SendTo`, and
22 `System.Net.Sockets.Socket.BeginSendTo` methods bind the current instance to the
23 local endpoint if the current instance has not previously been bound.

24

25]

26 Exceptions

| Exception | Condition |
|---|--|
| <code>System.ArgumentNullException</code> | <i>localEP</i> is null. |
| <code>System.Net.Sockets.SocketException</code> | An error occurred while accessing the socket. [Note: For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |

| | |
|--|---|
| | |
| System.ObjectDisposedException | The current instance has been disposed. |
| System.Security.SecurityException | A caller in the call stack does not have the required permission. |

1

2 **Permissions**

| Permission | Description |
|------------------------------------|--|
| System.Net.SocketPermission | Requires permission to accept connections on the endpoint defined by <i>localEP</i> . See <code>System.Net.NetworkAccess.Accept</code> . |

3

4

1 Socket.Close() Method

```
2 [ILAsm]  
3 .method public hidebysig instance void Close()  
4 [C#]  
5 public void Close()
```

6 Summary

7 Closes the current instance and releases all managed and unmanaged resources
8 allocated by the current instance.

9 Description

10 This method calls the `System.Net.Sockets.Socket.Dispose(System.Boolean)` method
11 with the argument set to `true`, which frees both managed and unmanaged resources
12 used by the current instance.

13
14 The socket attempts to perform a graceful closure when the
15 `System.Net.Sockets.SocketOptionName.Linger` socket option is enabled and set to a
16 non-zero linger time. In all other cases, closure is forced and any pending data is lost.

17

1 Socket.Connect(System.Net.EndPoint)

2 Method

```
3 [ILAsm]  
4 .method public hidebysig instance void Connect(class System.Net.EndPoint  
5 remoteEP)  
  
6 [C#]  
7 public void Connect(EndPoint remoteEP)
```

8 Summary

9 Associates the current instance with a remote endpoint.

10 Parameters

| Parameter | Description |
|-----------------|---|
| <i>remoteEP</i> | The System.Net.EndPoint associated with the socket to connect to. |

11 Description

13 This method sets the System.Net.Sockets.Socket.RemoteEndPoint property of the
14 current instance to *remoteEP*.

15
16 [Note: For connection-oriented protocols, this method establishes a connection between
17 the current instance and the socket associated with *remoteEP*. This method is used only
18 on the client-side. The System.Net.Sockets.Socket.Accept method establishes the
19 connection on the server-side. Once the connection has been made, data can be sent
20 using the System.Net.Sockets.Socket.Send method, and received using the
21 System.Net.Sockets.Socket.Receive method.

22
23 For connectionless protocols, the System.Net.Sockets.Socket.Connect method can be
24 used from both client and server-sides, allowing the use of the
25 System.Net.Sockets.Socket.Send method instead of the
26 System.Net.Sockets.Socket.SendTo method. The
27 System.Net.Sockets.Socket.RemoteEndPoint property is set to *remoteEP* and the
28 System.Net.Sockets.Socket.LocalEndPoint property is set to a value determined by
29 the protocol; however, a connection is not established. Subsequent data is required to
30 be received on the endpoint set in the System.Net.Sockets.Socket.LocalEndPoint
31 property.

32]

34 Exceptions

| Exception | Condition |
|-----------|-----------|
|-----------|-----------|

| | |
|---|--|
| System.ArgumentNullException | <i>remoteEP</i> is null. |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |
| System.Security.SecurityException | A caller in the call stack does not have the required permission. |

1

2 Permissions

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to make a connection to the endpoint defined by <i>remoteEP</i> . See <code>System.Net.NetworkAccess.Connect</code> . |

3

4

1 Socket.Dispose(System.Boolean) Method

```
2 [ILAsm]  
3 .method family hidebysig virtual void Dispose(bool disposing)  
4 [C#]  
5 protected virtual void Dispose(bool disposing)
```

6 Summary

7 Closes the current instance, releases the unmanaged resources allocated by the current
8 instance, and optionally releases the managed resources.

9 Parameters

| Parameter | Description |
|------------------|--|
| <i>disposing</i> | A System.Boolean. Specify true to release both managed and unmanaged resources; false to release only unmanaged resources. |

11 Behaviors

12 This method closes the current System.Net.Sockets.Socket instance and releases all
13 unmanaged resources allocated by the current instance. When *disposing* is true, this
14 method also releases all resources held by any managed objects allocated by the current
15 instance.

17 Default

18 This method closes the current System.Net.Sockets.Socket instance but does not
19 release any managed resources.

21 How and When to Override

22 The System.Net.Sockets.Socket.Dispose method can be called multiple times by
23 other objects. When overriding this method, do not reference objects that have been
24 previously disposed in an earlier call.

26 Usage

1 Use this method to release resources allocated by the current instance.

2

3

1 Socket.EndAccept(System.IAsyncResult)

2 Method

```
3 [ILAsm]  
4 .method public hidebysig instance class System.Net.Sockets.Socket  
5 EndAccept(class System.IAsyncResult asyncResult)  
  
6 [C#]  
7 public Socket EndAccept(IAsyncResult asyncResult)
```

8 Summary

9 Ends an asynchronous call to accept an incoming connection request.

10 Parameters

| Parameter | Description |
|--------------------|---|
| <i>asyncResult</i> | A System.IAsyncResult object that holds the state information for the asynchronous operation. |

11 Return Value

13 A new connected System.Net.Sockets.Socket instance.

14 Description

15 This method blocks if the asynchronous operation has not completed.

16
17 The System.Net.Sockets.Socket.EndAccept method completes an asynchronous
18 request that was started with a call to the System.Net.Sockets.Socket.BeginAccept
19 method. The object specified for the *asyncResult* parameter is required to be the same
20 object as was returned by the System.Net.Sockets.Socket.BeginAccept method call
21 that began the request.

22
23 If the System.Net.Sockets.Socket.EndAccept method is invoked via the
24 System.AsyncCallback delegate specified to the
25 System.Net.Sockets.Socket.BeginAccept method, the *asyncResult* parameter is the
26 System.IAsyncResult argument passed to the delegate's method.

27 Exceptions

| Exception | Condition |
|------------------------------|-----------------------------|
| System.ArgumentNullException | <i>asyncResult</i> is null. |

| | |
|---|---|
| System.ArgumentException | <i>asyncResult</i> was not returned by the current instance from a call to the <code>System.Net.Sockets.Socket.BeginAccept</code> method. |
| System.InvalidOperationException | <code>System.Net.Sockets.Socket.EndAccept</code> was previously called for this operation. |
| System.Net.Sockets.SocketException | An error occurred during the operation. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Example**

3 For an outline of an asynchronous operation, see the
 4 `System.Net.Sockets.Socket.BeginAccept` method. For the complete example, which
 5 uses the `System.Net.Sockets.Socket.EndAccept` method, see the
 6 `System.Net.Sockets.Socket` class overview.

7

1 Socket.EndConnect(System.IAsyncResult)

2 Method

```
3 [IAsm]  
4 .method public hidebysig instance void EndConnect(class  
5 System.IAsyncResult asyncResult)  
  
6 [C#]  
7 public void EndConnect(IAsyncResult asyncResult)
```

8 Summary

9 Ends an asynchronous call to associate the current instance with a remote endpoint.

10 Parameters

| Parameter | Description |
|--------------------|---|
| <i>asyncResult</i> | A System.IAsyncResult object that holds the state information for the asynchronous operation. |

11 Description

13 This method blocks if the asynchronous operation has not completed.

14
15 The System.Net.Sockets.Socket.EndConnect method completes an asynchronous
16 request that was started with a call to the System.Net.Sockets.Socket.BeginConnect
17 method. The object specified for the *asyncResult* parameter is required to be the same
18 object as was returned by the System.Net.Sockets.Socket.BeginConnect method call
19 that began the request.

20
21 If the System.Net.Sockets.Socket.EndConnect method is invoked via the
22 System.AsyncCallback delegate specified to the
23 System.Net.Sockets.Socket.BeginConnect method, the *asyncResult* parameter is the
24 System.IAsyncResult argument passed to the delegate's method.

25 Exceptions

| Exception | Condition |
|-------------------------------------|---|
| System.ArgumentNullException | <i>asyncResult</i> is null. |
| System.ArgumentException | <i>asyncResult</i> was not returned by the current instance from a call to the System.Net.Sockets.Socket.BeginConnect method. |

| | |
|---|--|
| System.InvalidOperationException | System.Net.Sockets.Socket.EndConnect was previously called for this operation. |
| System.Net.Sockets.SocketException | An error occurred during the operation. [<i>Note:</i> For additional information on causes of the SocketException, see the System.Net.Sockets.SocketException class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

1
2
3
4
5
6
7

Example

For an outline of an asynchronous operation, see the System.Net.Sockets.Socket.BeginAccept method. For the complete example, which uses the System.Net.Sockets.Socket.EndConnect method, see the System.Net.Sockets.Socket class overview.

1 Socket.EndReceive(System.IAsyncResult)

2 Method

```
3 [ILAsm]  
4 .method public hidebysig instance int32 EndReceive(class  
5 System.IAsyncResult asyncResult)  
  
6 [C#]  
7 public int EndReceive(IAsyncResult asyncResult)
```

8 Summary

9 Ends an asynchronous call to receive data from a socket.

10 Parameters

| Parameter | Description |
|--------------------|---|
| <i>asyncResult</i> | A System.IAsyncResult object that holds the state information for the asynchronous operation. |

11 Return Value

13 A System.Int32 containing the number of bytes received.

14 Description

15 This method blocks if the asynchronous operation has not completed.

16
17 The System.Net.Sockets.Socket.EndReceive method completes an asynchronous
18 request that was started with a call to the System.Net.Sockets.Socket.BeginReceive
19 method. The object specified for the *asyncResult* parameter is required to be the same
20 object as was returned by the System.Net.Sockets.Socket.BeginReceive method call
21 that began the request.

22
23 If the System.Net.Sockets.Socket.EndReceive method is invoked via the
24 System.AsyncCallback delegate specified to the
25 System.Net.Sockets.Socket.BeginReceive method, the *asyncResult* parameter is the
26 System.IAsyncResult argument passed to the delegate's method.

27 Exceptions

| Exception | Condition |
|------------------------------|-----------------------------|
| System.ArgumentNullException | <i>asyncResult</i> is null. |

| | |
|---|---|
| System.ArgumentException | <i>asyncResult</i> was not returned by the current instance from a call to the <code>System.Net.Sockets.Socket.BeginReceive</code> method. |
| System.InvalidOperationException | <code>System.Net.Sockets.Socket.EndReceive</code> was previously called for this operation. |
| System.Net.Sockets.SocketException | An error occurred during the operation. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Example**

3 For an outline of an asynchronous operation, see the
 4 `System.Net.Sockets.Socket.BeginAccept` method. For the complete example, which
 5 uses the `System.Net.Sockets.Socket.EndReceive` method, see the
 6 `System.Net.Sockets.Socket` class overview.

7

Socket.EndReceiveFrom(System.IAsyncResult, System.Net.EndPoint&) Method

```
[ILAsm]
.method public hidebysig instance int32 EndReceiveFrom(class
System.IAsyncResult asyncResult, class System.Net.EndPoint& endPoint)

[C#]
public int EndReceiveFrom(IAsyncResult asyncResult, ref EndPoint endPoint)
```

Summary

Ends an asynchronous call to receive data from a socket and store the endpoint associated with the socket that sent the data.

Parameters

| Parameter | Description |
|--------------------|--|
| <i>asyncResult</i> | A <code>System.IAsyncResult</code> object that holds the state information for the asynchronous operation. |
| <i>endPoint</i> | A reference to the <code>System.Net.EndPoint</code> associated with the socket that sent the data. |

Return Value

A `System.Int32` containing the number of bytes received.

Description

This method blocks if the asynchronous operation has not completed.

The `System.Net.Sockets.Socket.EndReceiveFrom` method completes an asynchronous request that was started with a call to the `System.Net.Sockets.Socket.BeginReceiveFrom` method. The object specified for the *asyncResult* parameter is required to be the same object as was returned by the `System.Net.Sockets.Socket.BeginReceiveFrom` method call that began the request.

If the `System.Net.Sockets.Socket.EndReceiveFrom` method is invoked via the `System.AsyncCallback` delegate specified to the `System.Net.Sockets.Socket.BeginReceiveFrom` method, the *asyncResult* parameter is the `System.IAsyncResult` argument passed to the delegate's method.

Exceptions

| Exception | Condition |
|---|---|
| System.ArgumentNullException | <i>asyncResult</i> is null. |
| System.ArgumentException | <i>asyncResult</i> was not returned by the current instance from a call to the <code>System.Net.Sockets.Socket.BeginReceiveFrom</code> method. |
| System.InvalidOperationException | <code>System.Net.Sockets.Socket.EndReceiveFrom</code> was previously called for this operation. |
| System.Net.Sockets.SocketException | An error occurred during the operation. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 Example

3

For an outline of an asynchronous operation, see the

4

`System.Net.Sockets.Socket.BeginAccept` method. For the complete example, see the

5

`System.Net.Sockets.Socket` class overview.

6

1 Socket.EndSend(System.IAsyncResult)

2 Method

```
3 [IAsm]  
4 .method public hidebysig instance int32 EndSend(class System.IAsyncResult  
5 asyncResult)  
  
6 [C#]  
7 public int EndSend(IAsyncResult asyncResult)
```

8 Summary

9 Ends an asynchronous call to send data to a connected socket.

10 Parameters

| Parameter | Description |
|--------------------|---|
| <i>asyncResult</i> | A System.IAsyncResult object that holds the state information for the asynchronous operation. |

11 Return Value

12 A System.Int32 containing the number of bytes sent.

14 Description

15 This method blocks if the asynchronous operation has not completed.

16
17 The System.Net.Sockets.Socket.EndSend method completes an asynchronous request
18 that was started with a call to the System.Net.Sockets.Socket.BeginSend method.
19 The object specified for the *asyncResult* parameter is required to be the same object as
20 was returned by the System.Net.Sockets.Socket.BeginSend method call that began
21 the request.

22
23 If the System.Net.Sockets.Socket.EndSend method is invoked via the
24 System.AsyncCallback delegate specified to the
25 System.Net.Sockets.Socket.BeginSend method, the *asyncResult* parameter is the
26 System.IAsyncResult argument passed to the delegate's method.

27 Exceptions

| Exception | Condition |
|------------------------------|-----------------------------|
| System.ArgumentNullException | <i>asyncResult</i> is null. |

| | |
|---|---|
| System.ArgumentException | <i>AsyncResult</i> was not returned by the current instance from a call to the <code>System.Net.Sockets.Socket.BeginSend</code> method. |
| System.InvalidOperationException | <code>System.Net.Sockets.Socket.EndSend</code> was previously called for this operation. |
| System.Net.Sockets.SocketException | An error occurred during the operation. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Example**

3 For an outline of an asynchronous operation, see the
4 `System.Net.Sockets.Socket.BeginAccept` method. For the complete example, which
5 uses the `System.Net.Sockets.Socket.EndSend` method, see the
6 `System.Net.Sockets.Socket` class overview.

7

1 Socket.EndSendTo(System.IAsyncResult)

2 Method

```
3 [IAsm]  
4 .method public hidebysig instance int32 EndSendTo(class  
5 System.IAsyncResult asyncResult)  
  
6 [C#]  
7 public int EndSendTo(IAsyncResult asyncResult)
```

8 Summary

9 Ends an asynchronous call to send data to a socket associated with a specified endpoint.

10 Parameters

| Parameter | Description |
|--------------------|---|
| <i>asyncResult</i> | A System.IAsyncResult object that holds the state information for the asynchronous operation. |

11 Return Value

12 A System.Int32 containing the number of bytes sent.

14 Description

15 This method blocks if the asynchronous operation has not completed.

16 The System.Net.Sockets.Socket.EndSendTo method completes an asynchronous
17 request that was started with a call to the System.Net.Sockets.Socket.BeginSendTo
18 method. The object specified for the *asyncResult* parameter is required to be the same
19 object as was returned by the System.Net.Sockets.Socket.BeginSendTo method call
20 that began the request.
21

22 If the System.Net.Sockets.Socket.EndSendTo method is invoked via the
23 System.AsyncCallback delegate specified to the
24 System.Net.Sockets.Socket.BeginSendTo method, the *asyncResult* parameter is the
25 System.IAsyncResult argument passed to the delegate's method.
26

27 Exceptions

| Exception | Condition |
|------------------------------|-----------------------------|
| System.ArgumentNullException | <i>asyncResult</i> is null. |

| | |
|---|---|
| System.ArgumentException | <i>asyncResult</i> was not returned by the current instance from a call to the <code>System.Net.Sockets.Socket.SendTo</code> method. |
| System.InvalidOperationException | <code>System.Net.Sockets.Socket.EndSendTo</code> was previously called for this operation. |
| System.Net.Sockets.SocketException | An error occurred during the operation. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Example**

3

For an outline of an asynchronous operation, see the

4

`System.Net.Sockets.Socket.BeginAccept` method. For the complete example, see the

5

`System.Net.Sockets.Socket` class overview.

6

1 Socket.Finalize() Method

```
2 [ILAsm]  
3 .method family hidebysig virtual void Finalize()  
4 [C#]  
5 ~Socket()
```

6 Summary

7 Closes the current instance and releases unmanaged resources allocated by the current
8 instance.

9 Description

10 [*Note:* Application code does not call this method; it is automatically invoked during
11 garbage collection unless finalization by the garbage collector has been disabled. For
12 more information, see `System.GC.SuppressFinalize`, and `System.Object.Finalize`.

13
14 This method calls `System.Net.Sockets.NetworkStream.Dispose(false)` to free
15 unmanaged resources used by the current instance.

16
17 This method overrides `System.Object.Finalize`.

18
19]

20

1 Socket.GetHashCode() Method

```
2 [ILAsm]  
3 .method public hidebysig virtual int32 GetHashCode()  
4 [C#]  
5 public override int GetHashCode()
```

6 Summary

7 Generates a hash code for the current instance.

8 Return Value

9 A `System.Int32` containing the hash code for the current instance.

10 Description

11 The algorithm used to generate the hash code is unspecified.

12

13 [*Note:* This method overrides `System.Object.GetHashCode()`.]

14

15

16

1
2 **Socket.GetSocketOption(System.Net.Sockets.**
3 **SocketOptionLevel,**
4 **System.Net.Sockets.SocketOptionName)**
5 **Method**

```
6 [ILAsm]  
7 .method public hidebysig instance object GetSocketOption(valuetype  
8 System.Net.Sockets.SocketOptionLevel optionLevel, valuetype  
9 System.Net.Sockets.SocketOptionName optionName)  
  
10 [C#]  
11 public object GetSocketOption(SocketOptionLevel optionLevel,  
12 SocketOptionName optionName)
```

13 **Summary**

14 Retrieves an object containing the value of the specified socket option.

15 **Parameters**

| Parameter | Description |
|--------------------|--|
| <i>optionLevel</i> | One of the values defined in the System.Net.Sockets.SocketOptionLevel enumeration. |
| <i>optionName</i> | One of the values defined in the System.Net.Sockets.SocketOptionName enumeration. |

16
17 **Return Value**

18 The following table describes the values returned by this method.

| optionName | Return value |
|---|--|
| Linger | An instance of the System.Net.Sockets.LingerOption class. |
| AddMembership -or- DropMembership | An instance of the System.Net.Sockets.MulticastOption class. |

| | |
|---|---|
| All other values defined in the <code>System.Net.Sockets.SocketOptionName</code> enumeration. | A <code>System.Int32</code> containing the value of the option. |
|---|---|

1

2 Description

3 Socket options determine the behavior of the current instance.

4

5 *optionLevel* and *optionName* are not independent. See the
6 `System.Net.Sockets.Socket.SetSocketOption(SocketOptionLevel,`
7 `SocketOptionName, Int32)` method for a listing of the values of the
8 `System.Net.Sockets.SocketOptionName` enumeration grouped by
9 `System.Net.Sockets.SocketOptionLevel`.

10 Exceptions

| Exception | Condition |
|---|--|
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

11

12 Example

13 The following example gets the state of the linger option and the size of the receive
14 buffer, changes the values of both, then gets the new values.

15

16 [C#]

```

17 using System;
18 using System.Net.Sockets;
19
20 class OptionTest{
21
22     public static void Main() {
23
24         // Get the current option values.
25         Socket someSocket =
26             new Socket(AddressFamily.InterNetwork,
27                 SocketType.Stream,
```

```

1         ProtocolType.Tcp);
2
3     LingerOption lingerOp =
4         (LingerOption)someSocket.GetSocketOption(
5             SocketOptionLevel.Socket,
6             SocketOptionName.Linger);
7
8     int receiveBuffer =
9         (int)someSocket.GetSocketOption(
10            SocketOptionLevel.Socket,
11            SocketOptionName.ReceiveBuffer);
12
13     Console.WriteLine(
14         "Linger option is {0} and set to {1} seconds.",
15         lingerOp.Enabled.ToString(),
16         lingerOp.LingerTime.ToString() );
17
18     Console.WriteLine(
19         "Size of the receive buffer is {0} bytes.",
20         receiveBuffer.ToString() );
21
22     // Change the options.
23     lingerOp = new LingerOption(true, 10);
24     someSocket.SetSocketOption(
25         SocketOptionLevel.Socket,
26         SocketOptionName.Linger,
27         lingerOp);
28
29     someSocket.SetSocketOption(
30         SocketOptionLevel.Socket,
31         SocketOptionName.ReceiveBuffer,
32         2048);
33
34     Console.WriteLine(
35         "The SetSocketOption method has been called.");
36
37     // Get the new option values.
38     lingerOp =
39         (LingerOption)someSocket.GetSocketOption(
40             SocketOptionLevel.Socket,
41             SocketOptionName.Linger);
42
43     receiveBuffer =
44         (int)someSocket.GetSocketOption(
45             SocketOptionLevel.Socket,
46             SocketOptionName.ReceiveBuffer);
47
48     Console.WriteLine(
49         "Linger option is now {0} and set to {1} seconds.",
50         lingerOp.Enabled.ToString(),
51         lingerOp.LingerTime.ToString());
52
53     Console.WriteLine(
54         "Size of the receive buffer is now {0} bytes.",
55         receiveBuffer.ToString());
56 }
57 }

```

1
2 The output is
3
4 Linger option is False and set to 0 seconds.
5
6
7 Size of the receive buffer is 8192 bytes.
8
9
10 The SetSocketOption method has been called.
11
12
13 Linger option is now True and set to 10 seconds.
14
15
16 Size of the receive buffer is now 2048 bytes.
17
18

1
2 **Socket.GetSocketOption(System.Net.Sockets.**
3 **SocketOptionLevel,**
4 **System.Net.Sockets.SocketOptionName,**
5 **System.Byte[]) Method**

```
6 [ILAsm]  
7 .method public hidebysig instance void GetSocketOption(valuetype  
8 System.Net.Sockets.SocketOptionLevel optionLevel, valuetype  
9 System.Net.Sockets.SocketOptionName optionName, class System.Byte[]  
10 optionValue)  
  
11 [C#]  
12 public void GetSocketOption(SocketOptionLevel optionLevel,  
13 SocketOptionName optionName, byte[] optionValue)
```

14 **Summary**

15 Retrieves the value of the specified socket option.

16 **Parameters**

| Parameter | Description |
|--------------------|--|
| <i>optionLevel</i> | One of the values defined in the System.Net.Sockets.SocketOptionLevel enumeration. |
| <i>optionName</i> | One of the values defined in the System.Net.Sockets.SocketOptionName enumeration. |
| <i>optionValue</i> | A System.Byte array that receives the value of the specified socket option. |

17
18 **Description**

19 Socket options determine the behavior of the current instance.
20
21 Upon successful completion, the array specified by the *optionValue* parameter contains
22 the value of the specified socket option.
23
24 When the length of the *optionValue* array is smaller than the number of bytes required
25 to store the value of the specified socket option, a
26 System.Net.Sockets.SocketException exception is thrown.

27 **Exceptions**

| Exception | Condition |
|---|---|
| System.Net.Sockets.SocketException | <p><i>optionValue</i> is too small to store the value of the specified socket option.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.ObjectDisposedException | <p>The current instance has been disposed.</p> |

1

2

1
2 **Socket.GetSocketOption(System.Net.Sockets.**
3 **SocketOptionLevel,**
4 **System.Net.Sockets.SocketOptionName,**
5 **System.Int32) Method**

```
6 [ILAsm]  
7 .method public hidebysig instance class System.Byte[]  
8 GetSocketOption(valuetype System.Net.Sockets.SocketOptionLevel  
9 optionLevel, valuetype System.Net.Sockets.SocketOptionName optionName,  
10 int32 optionLength)  
  
11 [C#]  
12 public byte[] GetSocketOption(SocketOptionLevel optionLevel,  
13 SocketOptionName optionName, int optionLength)
```

14 **Summary**

15 Retrieves the value of the specified socket option.

16 **Parameters**

| Parameter | Description |
|---------------------|---|
| <i>optionLevel</i> | One of the values defined in the <code>System.Net.Sockets.SocketOptionLevel</code> enumeration. |
| <i>optionName</i> | One of the values defined in the <code>System.Net.Sockets.SocketOptionName</code> enumeration. |
| <i>optionLength</i> | A <code>System.Int32</code> containing the maximum length, in bytes, of the value of the specified socket option. |

17
18 **Return Value**

19 A `System.Byte` array containing the value of the specified socket option.

20 **Description**

21 Socket options determine the behavior of the current instance.
22
23 The *optionLength* parameter is used to allocate an array to store the value of the
24 specified option. When this value is smaller than the number of bytes required to store
25 the value of the specified option, a `System.Net.Sockets.SocketException` exception is
26 thrown. When this value is greater than or equal to the number of bytes required to

- 1 store the value of the specified option, the array returned by this method is allocated to
- 2 be exactly the required length.

3 Exceptions

| Exception | Condition |
|---|--|
| System.Net.Sockets.SocketException | <p><i>optionLength</i> is smaller than the number of bytes required to store the value of the specified socket option.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.ObjectDisposedException | The current instance has been disposed. |

4

5

1 Socket.IOControl(System.Int32, 2 System.Byte[], System.Byte[]) Method

```
3 [ILAsm]  
4 .method public hidebysig instance int32 IOControl(int32 ioControlCode,  
5 class System.Byte[] optionInValue, class System.Byte[] optionOutValue)  
  
6 [C#]  
7 public int IOControl(int ioControlCode, byte[] optionInValue, byte[]  
8 optionOutValue)
```

9 Summary

10 Provides low-level access to the socket, the transport protocol, or the communications
11 subsystem.

12 Parameters

| Parameter | Description |
|-----------------------|--|
| <i>ioControlCode</i> | A <code>System.Int32</code> containing the control code of the operation to perform. |
| <i>optionInValue</i> | A <code>System.Byte</code> array containing the input data required by the operation. |
| <i>optionOutValue</i> | A <code>System.Byte</code> array containing the output data supplied by the operation. |

14 Return Value

15 A `System.Int32` containing the length of the *optionOutValue* array after the method
16 returns.

17 Description

18 If an attempt is made to change the blocking mode of the current instance, an exception
19 is thrown. Use the `System.Net.Sockets.Socket.Blocking` property to change the
20 blocking mode.

21
22 The control codes and their requirements are implementation defined. Do not use this
23 method if platform independence is a requirement.

24
25 [Note: Input data is not required for all control codes. Output data is not supplied by all
26 control codes and, if not supplied, the return value is 0.]

29 Exceptions

| Exception | Condition |
|---|--|
| System.InvalidOperationException | An attempt was made to change the blocking mode. [<i>Note:</i> Use the <code>System.Net.Sockets.Socket.Blocking</code> property to change the blocking mode.] |
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |

1

2 Example

3 The following example gets the number of bytes of available data to be read and writes
4 the result to the console on a Windows system. The remote endpoint (`remoteEndpoint`)
5 to connect to might need to be changed to a value that is valid on the current system.

6

7 [C#]

8 using System;

9 using System.Net;

10 using System.Net.Sockets;

11

12 class App {

13

14 static void Main() {

15

16 IPAddress remoteAddress =

17 Dns.Resolve(Dns.GetHostName()).AddressList[0];

18

19 IPEndPoint remoteEndpoint =

20 new IPEndPoint(remoteAddress, 80);

21

22 Socket someSocket =

23 new Socket(AddressFamily.InterNetwork,

24 SocketType.Stream,

```

1         ProtocolType.Tcp);
2
3     someSocket.Connect(remoteEndpoint);
4
5     int fionRead = 0x4004667F;
6     byte[]inValue = {0x00, 0x00, 0x00, 0x00};
7     byte[]outValue = {0x00, 0x00, 0x00, 0x00};
8
9     someSocket.IOControl(fionRead, inValue, outValue);
10
11     uint bytesAvail = BitConverter.ToUInt32(outValue, 0);
12
13     Console.WriteLine(
14         "There are {0} bytes available to be read.",
15         bytesAvail.ToString() );
16     }
17 }

```

19 The output is

20

21 There are 0 bytes available to be read.

22

23 Permissions

| Permission | Description |
|---|---|
| System.Security.Permissions.SecurityPermission | Requires permission to access unmanaged code. See <code>System.Security.Permissions.SecurityPermissionFlag.UnmanagedCode</code> . |

24

25

1 Socket.Listen(System.Int32) Method

```
2 [ILAsm]  
3 .method public hidebysig instance void Listen(int32 backlog)  
4 [C#]  
5 public void Listen(int backlog)
```

6 Summary

7 Places the current instance into the listening state where it waits for incoming
8 connection requests.

9 Parameters

| Parameter | Description |
|----------------|---|
| <i>backlog</i> | A System.Int32 containing the maximum length of the queue of pending connections. |

11 Description

12 Once this method is called, incoming connection requests are placed in a queue. The
13 maximum size of the queue is specified by the *backlog* parameter. The size of the queue
14 is limited to legal values by the underlying protocol. Illegal values of the *backlog*
15 parameter are replaced with a legal value, which is implementation defined.

16
17 If a connection request arrives and the queue is full, a
18 System.Net.Sockets.SocketException is thrown on the client.

19
20 A socket in the listening state has no remote endpoint associated with it. Attempting to
21 access the System.Net.Sockets.Socket.RemoteEndPoint property throws a
22 System.Net.Sockets.SocketException exception.

23
24 This method is ignored if called more than once on the current instance.

25
26 [Note: This method is used only on the server-side of connection-oriented protocols. Call
27 the System.Net.Sockets.Socket.Bind method before this method is called the first
28 time. Call the System.Net.Sockets.Socket.Listen method before the first call to the
29 System.Net.Sockets.Socket.Accept method.

30
31]

32 Exceptions

| Exception | Condition |
|-----------|-----------|
|-----------|-----------|

| | |
|--|---|
| <p>System.Net.Sockets.SocketException</p> | <p>The <code>System.Net.Sockets.Socket.Connected</code> property of the current instance is true.-or-</p> <p><code>Bind</code> has not been called on the current instance.-or-</p> <p>An error occurred while accessing the socket. <i>[Note: For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</i></p> |
| <p>System.ObjectDisposedException</p> | <p>The current instance has been disposed.</p> |

1

2

1 Socket.Poll(System.Int32, 2 System.Net.Sockets.SelectMode) Method

```
3 [ILAsm]  
4 .method public hidebysig instance bool Poll(int32 microseconds, valuetype  
5 System.Net.Sockets.SelectMode mode)  
  
6 [C#]  
7 public bool Poll(int microseconds, SelectMode mode)
```

8 Summary

9 Determines the read, write, or error status of the current instance.

10 Parameters

| Parameter | Description |
|---------------------|---|
| <i>microSeconds</i> | A <code>System.Int32</code> containing the time to wait for a response, in microseconds. Set the <i>microSeconds</i> parameter to a negative value to wait indefinitely for a response. |
| <i>mode</i> | One of the values defined in the <code>System.Net.Sockets.SelectMode</code> enumeration. |

11 12 Return Value

13 A `System.Boolean` where `true` indicates the current instance satisfies at least one of the
14 conditions in the following table corresponding to the specified
15 `System.Net.Sockets.SelectMode` value; otherwise, `false`. `false` is returned if the
16 status of the current instance cannot be determined within the time specified by
17 *microSeconds*.

| SelectMode value | Condition |
|------------------|--|
| SelectRead | Data is available for reading (includes out-of-band data if the <code>System.Net.Sockets.SocketOptionName.OutOfBandInline</code> value defined in the <code>System.Net.Sockets.SocketOptionName</code> enumeration is set). -or- The socket is in the listening state with a pending connection, and the <code>System.Net.Sockets.Socket.Accept</code> method has been called and is guaranteed to succeed without blocking. |

| | |
|-------------|---|
| | <p>-or-</p> <p>The connection has been closed, reset, or terminated.</p> |
| SelectWrite | <p>Data can be sent.</p> <p>-or-</p> <p>A non-blocking <code>System.Net.Sockets.Socket.Connect</code> method is being processed and the connection has succeeded.</p> |
| SelectError | <p>The <code>System.Net.Sockets.SocketOptionName.OutOfBandInline</code> value defined in the <code>System.Net.Sockets.SocketOptionName</code> enumeration is not set and out-of-band data is available.</p> <p>-or-</p> <p>A non-blocking <code>System.Net.Sockets.Socket.Connect</code> method is being processed and the connection has failed.</p> |

1

2 Exceptions

| Exception | Condition |
|---|---|
| System.NotSupportedException | <i>mode</i> is not one of the values defined in the <code>System.Net.Sockets.SelectMode</code> enumeration. |
| System.Net.Sockets.SocketException | <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.ObjectDisposedException | The current instance has been disposed. |

3

4

1 Socket.Receive(System.Byte[], 2 System.Int32, 3 System.Net.Sockets.SocketFlags) Method

```
4 [ILAsm]  
5 .method public hidebysig instance int32 Receive(class System.Byte[]  
6 buffer, int32 size, valuetype System.Net.Sockets.SocketFlags socketFlags)  
7  
8 [C#]  
9 public int Receive(byte[] buffer, int size, SocketFlags socketFlags)
```

9 Summary

10 Receives data from a socket.

11 Parameters

| Parameter | Description |
|--------------------|---|
| <i>buffer</i> | A System.Byte array to store data received from the socket. |
| <i>size</i> | A System.Int32 containing the number of bytes to receive. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.OutOfBand, or System.Net.Sockets.SocketFlags.Peek. |

12

13 Return Value

14 A System.Int32 containing the number of bytes received.

15 Description

16 This method is equivalent to System.Net.Sockets.Socket.Receive(*buffer*, 0, *size*,
17 *socketFlags*).

18 Exceptions

| Exception | Condition |
|------------------------------|------------------------|
| System.ArgumentNullException | <i>buffer</i> is null. |

| | |
|---|---|
| System.ArgumentOutOfRangeException | <p><i>size</i> < 0.</p> <p>-or-</p> <p><i>size</i> > <i>buffer.Length</i>.</p> |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to accept connections. See <code>System.Net.NetworkAccess.Accept</code> . |

3

4

1 Socket.Receive(System.Byte[], 2 System.Net.Sockets.SocketFlags) Method

```
3 [ILAsm]  
4 .method public hidebysig instance int32 Receive(class System.Byte[]  
5 buffer, valuetype System.Net.Sockets.SocketFlags socketFlags)  
  
6 [C#]  
7 public int Receive(byte[] buffer, SocketFlags socketFlags)
```

8 Summary

9 Receives data from a socket.

10 Parameters

| Parameter | Description |
|--------------------|---|
| <i>buffer</i> | A System.Byte array to store data received from the socket. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.OutOfBand, OR System.Net.Sockets.SocketFlags.Peek. |

11 12 Return Value

13 A System.Int32 containing the number of bytes received.

14 Description

15 This method is equivalent to System.Net.Sockets.Socket.Receive(*buffer*, 0,
16 *buffer.Length*, *socketFlags*).

17 Exceptions

| Exception | Condition |
|----------------------------------|--|
| System.ArgumentNullException | <i>buffer</i> is null. |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |

| | |
|---|---|
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to accept connections. [<i>Note:</i> See <code>System.Net.NetworkAccess.Accept</code> .] |

3

4

1 Socket.Receive(System.Byte[], 2 System.Int32, System.Int32, 3 System.Net.Sockets.SocketFlags) Method

```
4 [ILAsm]  
5 .method public hidebysig instance int32 Receive(class System.Byte[]  
6 buffer, int32 offset, int32 size, valuetype System.Net.Sockets.SocketFlags  
7 socketFlags)  
  
8 [C#]  
9 public int Receive(byte[] buffer, int offset, int size, SocketFlags  
10 socketFlags)
```

11 Summary

12 Receives data from a socket.

13 Parameters

| Parameter | Description |
|--------------------|---|
| <i>buffer</i> | A System.Byte array to store data received from the socket. |
| <i>offset</i> | A System.Int32 containing the zero-based position in <i>buffer</i> to begin storing the received data. |
| <i>size</i> | A System.Int32 containing the number of bytes to receive. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.OutOfBand, or System.Net.Sockets.SocketFlags.Peek. |

14 15 Return Value

16 A System.Int32 containing the number of bytes received.

17 Description

18 The System.Net.Sockets.Socket.LocalEndPoint property is required to be set before
19 this method is called.

20
21 The System.Net.Sockets.Socket.Blocking property of the socket determines the
22 behavior of this method when no incoming data is available. When false, the

1 `System.Net.Sockets.SocketException` exception is thrown. When `true`, this method
2 blocks and waits for data to arrive.
3
4 For `System.Net.Sockets.SocketType.Stream` socket types, if the remote socket was
5 shut down gracefully, and all data was received, this method immediately returns zero,
6 regardless of the blocking state.
7
8 For message-oriented sockets, if the message is larger than the size of *buffer*, the buffer
9 is filled with the first part of the message, and the
10 `System.Net.Sockets.SocketException` exception is thrown. For unreliable protocols,
11 the excess data is lost; for reliable protocols, the data is retained by the service
12 provider.
13
14 When the `System.Net.Sockets.SocketFlags.OutOfBand` flag is specified as part of the
15 *socketFlags* parameter and the socket is configured for in-line reception of out-of-band
16 (OOB) data (using the `System.Net.Sockets.SocketOptionName.OutOfBandInline`
17 socket option) and OOB data is available, only OOB data is returned.
18
19 When the `System.Net.Sockets.SocketFlags.Peek` flag is specified as part of the
20 *socketFlags* parameter, available data is copied into *buffer* but is not removed from the
21 system buffer.

22 Exceptions

| Exception | Condition |
|---|--|
| System.ArgumentNullException | <i>buffer</i> is null. |
| System.ArgumentOutOfRangeException | <i>offset</i> < 0. -or- <i>offset</i> > <i>buffer.Length</i> . -or- <i>size</i> < 0. -or- <i>size</i> > <i>buffer.Length</i> - <i>offset</i> . |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | <i>socketFlags</i> is not a valid combination of values. |

| | |
|--|---|
| | <p>-or-</p> <p>The <code>System.Net.Sockets.Socket.LocalEndPoint</code> property was not set.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to accept a connection on the endpoint defined by the <code>System.Net.Sockets.Socket.LocalEndPoint</code> property of the current instance. See <code>System.Net.NetworkAccess.Accept</code> . |

3

4

1 Socket.Receive(System.Byte[]) Method

```
2 [ILAsm]  
3 .method public hidebysig instance int32 Receive(class System.Byte[]  
4 buffer)  
5 [C#]  
6 public int Receive(byte[] buffer)
```

7 Summary

8 Receives data from a socket.

9 Parameters

| Parameter | Description |
|---------------|---|
| <i>buffer</i> | A System.Byte array to store data received from the socket. |

10

11 Return Value

12 A System.Int32 containing the number of bytes received.

13 Description

14 This method is equivalent to System.Net.Sockets.Socket.Receive(*buffer*, 0,
15 *buffer.Length*, System.Net.Sockets.SocketFlags.None).

16 Exceptions

| Exception | Condition |
|---|---|
| System.ArgumentNullException | <i>buffer</i> is null. |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [Note: For additional information on causes of the SocketException, see the System.Net.Sockets.SocketException class.] |

| | |
|--|--|
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to accept connections. See <code>System.Net.NetworkAccess.Accept</code> . |

3

4

1 Socket.ReceiveFrom(System.Byte[], 2 System.Net.EndPoint&) Method

```
3 [ILAsm]  
4 .method public hidebysig instance int32 ReceiveFrom(class System.Byte[]  
5 buffer, class System.Net.EndPoint& remoteEP)  
  
6 [C#]  
7 public int ReceiveFrom(byte[] buffer, ref EndPoint remoteEP)
```

8 Summary

9 Receives data from a socket and, for connectionless protocols, stores the endpoint
10 associated with the socket that sent the data.

11 Parameters

| Parameter | Description |
|-----------------|---|
| <i>buffer</i> | A System.Byte array to store data received from the socket. |
| <i>remoteEP</i> | A reference to the System.Net.EndPoint associated with the socket that sent the data. |

12

13 Return Value

14 A System.Int32 containing the number of bytes received.

15 Description

16 This method is equivalent to System.Net.Sockets.Socket.ReceiveFrom(*buffer*, 0,
17 *buffer.Length*, System.Net.Sockets.SocketFlags.None, *remoteEP*).

18 Exceptions

| Exception | Condition |
|---|--|
| System.ArgumentNullException | <i>buffer</i> or <i>remoteEP</i> is null. |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [Note: For additional information on causes of the SocketException, see the |

| | |
|---------------------------------------|--|
| | System.Net.Sockets.SocketException class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to accept connections from the endpoint defined by <i>remoteEP</i> . See System.Net.NetworkAccess.Accept. |

3

4

1 Socket.ReceiveFrom(System.Byte[], 2 System.Net.Sockets.SocketFlags, 3 System.Net.EndPoint&) Method

```
4 [ILAsm]  
5 .method public hidebysig instance int32 ReceiveFrom(class System.Byte[]  
6 buffer, valuetype System.Net.Sockets.SocketFlags socketFlags, class  
7 System.Net.EndPoint& remoteEP)  
  
8 [C#]  
9 public int ReceiveFrom(byte[] buffer, SocketFlags socketFlags, ref  
10 EndPoint remoteEP)
```

11 Summary

12 Receives data from a socket and, for connectionless protocols, stores the endpoint
13 associated with the socket that sent the data.

14 Parameters

| Parameter | Description |
|--------------------|---|
| <i>buffer</i> | A System.Byte array to store data received from the socket. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.OutOfBand, or System.Net.Sockets.SocketFlags.Peek. |
| <i>remoteEP</i> | A reference to the System.Net.EndPoint associated with the socket that sent the data. |

15 16 Return Value

17 A System.Int32 containing the number of bytes received.

18 Description

19 This method is equivalent to System.Net.Sockets.Socket.ReceiveFrom(*buffer*, 0,
20 *buffer.Length*, *socketFlags*, *remoteEP*).

21 Exceptions

| Exception | Condition |
|---|---|
| System.ArgumentNullException | <i>buffer</i> or <i>remoteEP</i> is null. |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> specified an invalid value.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 Permissions

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to accept connections from the endpoint defined by <i>remoteEP</i> . See <code>System.Net.NetworkAccess.Accept</code> . |

3

4

1 Socket.ReceiveFrom(System.Byte[], 2 System.Int32, 3 System.Net.Sockets.SocketFlags, 4 System.Net.EndPoint&) Method

```
5 [ILAsm]  
6 .method public hidebysig instance int32 ReceiveFrom(class System.Byte[]  
7 buffer, int32 size, valuetype System.Net.Sockets.SocketFlags socketFlags,  
8 class System.Net.EndPoint& remoteEP)  
  
9 [C#]  
10 public int ReceiveFrom(byte[] buffer, int size, SocketFlags socketFlags,  
11 ref EndPoint remoteEP)
```

12 Summary

13 Receives data from a socket and, for connectionless protocols, stores the endpoint
14 associated with the socket that sent the data.

15 Parameters

| Parameter | Description |
|--------------------|---|
| <i>buffer</i> | A System.Byte array to store data received from the socket. |
| <i>size</i> | A System.Int32 containing the number of bytes to receive. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.OutOfBand, or System.Net.Sockets.SocketFlags.Peek. |
| <i>remoteEP</i> | A reference to the System.Net.EndPoint associated with the socket that sent the data. |

16 17 Return Value

18 A System.Int32 containing the number of bytes received.

19 Description

20 This method is equivalent to System.Net.Sockets.Socket.ReceiveFrom(*buffer*, 0, *size*,
21 *socketFlags*, *remoteEP*).

1 Exceptions

| Exception | Condition |
|---|--|
| System.ArgumentNullException | <i>buffer</i> or <i>remoteEP</i> is null. |
| System.ArgumentOutOfRangeException | <i>size</i> < 0. -or- <i>size</i> > <i>buffer.Length</i> . |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | <i>socketFlags</i> is not a valid combination of values. -or- An error occurred while accessing the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

2

3 Permissions

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to accept connections from the endpoint defined by <i>remoteEP</i> . See <code>System.Net.NetworkAccess.Accept</code> . |

4

5

1 Socket.ReceiveFrom(System.Byte[], 2 System.Int32, System.Int32, 3 System.Net.Sockets.SocketFlags, 4 System.Net.EndPoint&) Method

```
5 [ILAsm]  
6 .method public hidebysig instance int32 ReceiveFrom(class System.Byte[]  
7 buffer, int32 offset, int32 size, valuetype System.Net.Sockets.SocketFlags  
8 socketFlags, class System.Net.EndPoint& remoteEP)  
  
9 [C#]  
10 public int ReceiveFrom(byte[] buffer, int offset, int size, SocketFlags  
11 socketFlags, ref EndPoint remoteEP)
```

12 Summary

13 Receives data from a socket and, for connectionless protocols, stores the endpoint
14 associated with the socket that sent the data.

15 Parameters

| Parameter | Description |
|--------------------|---|
| <i>buffer</i> | A System.Byte array to store data received from the socket. |
| <i>offset</i> | A System.Int32 containing the zero-based position in <i>buffer</i> to begin storing the received data. |
| <i>size</i> | A System.Int32 containing the number of bytes to receive. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.OutOfBand, or System.Net.Sockets.SocketFlags.Peek. |
| <i>remoteEP</i> | A reference to the System.Net.EndPoint associated with the socket that sent the data. |

16 17 Return Value

18 A System.Int32 containing the number of bytes received.

19 Description

1 For connectionless protocols, when this method successfully completes, *remoteEP*
2 contains the endpoint associated with the socket that sent the data.
3
4 For connection-oriented protocols, *remoteEP* is left unchanged.
5
6 The `System.Net.Sockets.Socket.LocalEndPoint` property is required to be set before
7 this method is called or a `System.Net.Sockets.SocketException` is thrown.
8
9 The `System.Net.Sockets.Socket.Blocking` property of the socket determines the
10 behavior of this method when no incoming data is available. When `false`, the
11 `System.Net.Sockets.SocketException` exception is thrown. When `true`, this method
12 blocks and waits for data to arrive.
13
14 For `System.Net.Sockets.SocketType.Stream` socket types, if the remote socket was
15 shut down gracefully, and all data was received, this method immediately returns zero,
16 regardless of the blocking state.
17
18 For message-oriented sockets, if the message is larger than the size of *buffer*, the buffer
19 is filled with the first part of the message, and the
20 `System.Net.Sockets.SocketException` exception is thrown. For unreliable protocols,
21 the excess data is lost; for reliable protocols, the data is retained by the service
22 provider.
23
24 When the `System.Net.Sockets.SocketFlags.OutOfBand` flag is specified as part of
25 the *socketFlags* parameter and the socket is configured for in-line reception of out-of-
26 band (OOB) data (using the
27 `System.Net.Sockets.SocketOptionName.OutOfBandInline` socket option) and OOB
28 data is available, only OOB data is returned.
29
30 When the `System.Net.Sockets.SocketFlags.Peek` flag is specified as part of the
31 *socketFlags* parameter, available data is copied into *buffer* but is not removed from the
32 system buffer.

33 **Exceptions**

| Exception | Condition |
|---|---|
| System.ArgumentNullException | <i>buffer</i> or <i>remoteEP</i> is null. |
| System.ArgumentOutOfRangeException | <i>offset</i> < 0. |
| | -or- |
| | <i>offset</i> > <i>buffer.Length</i> . |
| | -or- |
| | <i>size</i> < 0. |
| | -or- |

| | |
|---|---|
| | <i>size > buffer.Length - offset.</i> |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>The <code>System.Net.Sockets.Socket.LocalEndPoint</code> property was not set.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | <p>Requires permission to accept a connection on the endpoint defined by the <code>System.Net.Sockets.Socket.LocalEndPoint</code> property of the current instance. See <code>System.Net.NetworkAccess.Accept</code>.</p> <p>Requires permission to make a connection to the endpoint defined by <i>remoteEP</i>. See</p> |

| | |
|--|-----------------------------------|
| | System.Net.NetworkAccess.Connect. |
|--|-----------------------------------|

1

2

1 Socket.Select(System.Collections.IList, 2 System.Collections.IList, 3 System.Collections.IList, System.Int32) 4 Method

```
5 [ILAsm]  
6 .method public hidebysig static void Select(class System.Collections.IList  
7 checkRead, class System.Collections.IList checkWrite, class  
8 System.Collections.IList checkError, int32 microseconds)  
  
9 [C#]  
10 public static void Select(IList checkRead, IList checkWrite, IList  
11 checkError, int microseconds)
```

12 Summary

13 Determines the read, write, or error status of a set of System.Net.Sockets.Socket
14 instances.

15 Parameters

| Parameter | Description |
|---------------------|--|
| <i>checkRead</i> | A System.Collections.IList object containing the System.Net.Sockets.Socket instances to check for read status. |
| <i>checkWrite</i> | A System.Collections.IList object containing the System.Net.Sockets.Socket instances to check for write status. |
| <i>checkError</i> | A System.Collections.IList object containing the System.Net.Sockets.Socket instances to check for error status. |
| <i>microSeconds</i> | A System.Int32 that specifies the time to wait for a response, in microseconds. Specify a negative value to wait indefinitely for the status to be determined. |

16 17 Description

18 Upon successful completion, this method removes all System.Net.Sockets.Socket
19 instances from the specified list that do not satisfy one of the conditions associated with
20 that list. The following table describes the conditions for each list.

| List | Condition to remain in list |
|------|-----------------------------|
|------|-----------------------------|

| | |
|-------------------|--|
| <i>checkRead</i> | <p>Data is available for reading (includes out-of-band data if the <code>System.Net.Sockets.SocketOptionName.OutOfBandInline</code> value defined in the <code>System.Net.Sockets.SocketOptionName</code> enumeration is set).</p> <p>-or-</p> <p>The socket is in the listening state with a pending connection, and the <code>System.Net.Sockets.Socket.Accept</code> method has been called and is guaranteed to succeed without blocking.</p> <p>-or-</p> <p>The connection has been closed, reset, or terminated.</p> |
| <i>checkWrite</i> | <p>Data can be sent.</p> <p>-or-</p> <p>A non-blocking <code>System.Net.Sockets.Socket.Connect</code> method is being processed and the connection has succeeded.</p> |
| <i>checkError</i> | <p>The <code>System.Net.Sockets.SocketOptionName.OutOfBandInline</code> value defined in the <code>System.Net.Sockets.SocketOptionName</code> enumeration is not set and out-of-band data is available.</p> <p>-or-</p> <p>A non-blocking <code>System.Net.Sockets.Socket.Connect</code> method is being processed and the connection has failed.</p> |

1
2
3
4
5
6
7
8
9
10
11
12
13

[*Note:* To determine the status of a specific `System.Net.Sockets.Socket` instance, check whether the instance remains in the list after the method returns.]

When the method cannot determine the status of all the `System.Net.Sockets.Socket` instances within the time specified in the *microseconds* parameter, the method removes all the `System.Net.Sockets.Socket` instances from all the lists and returns.

At least one of *checkRead*, *checkWrite*, or *checkError*, is required to contain at least one `System.Net.Sockets.Socket` instance. The other parameters can be empty or null.

Exceptions

| Exception | Condition |
|---|---|
| System.ArgumentNullException | All of the following parameters are null or empty: <i>checkRead</i> , <i>checkWrite</i> , and <i>checkError</i> . |
| System.Net.Sockets.SocketException | An error occurred while accessing one of the sockets. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |

1

2 Example

3 The following example determines the status of the socket instance named `socket3` and
4 writes the result to the console.

5

6 [C#]

```

7 using System;
8 using System.Collections;
9 using System.Net.Sockets;
10
11 class SelectTest {
12
13     public static void Main() {
14
15         Socket socket1 =
16             new Socket(AddressFamily.InterNetwork,
17                       SocketType.Stream,
18                       ProtocolType.Tcp);
19         Socket socket2 =
20             new Socket(AddressFamily.InterNetwork,
21                       SocketType.Stream,
22                       ProtocolType.Tcp);
23         Socket socket3 =
24             new Socket(AddressFamily.InterNetwork,
25                       SocketType.Stream,
26                       ProtocolType.Tcp);
27
28         ArrayList readList = new ArrayList();
29         ArrayList writeList = new ArrayList();
30         ArrayList errorList = new ArrayList();
31
32         readList.Add(socket1);
33         readList.Add(socket2);
34         readList.Add(socket3);
35         errorList.Add(socket1);
36         errorList.Add(socket3);
37
38         // readList.Contains(Socket3) returns true

```

```

1      // if Socket3 is in ReadList.
2      Console.WriteLine(
3          "socket3 is placed in readList and errorList.");
4      Console.WriteLine(
5          "socket3 is {0}in readList.",
6          readList.Contains(socket3) ? "" : "not " );
7      Console.WriteLine(
8          "socket3 is {0}in writeList.",
9          writeList.Contains(socket3) ? "" : "not " );
10     Console.WriteLine(
11         "socket3 is {0}in errorList.",
12         errorList.Contains(socket3) ? "" : "not " );
13
14     Socket.Select(readList, writeList, errorList, 10);
15     Console.WriteLine("The Select method has been called.");
16     Console.WriteLine(
17         "socket3 is {0}in readList.",
18         readList.Contains(socket3) ? "" : "not " );
19     Console.WriteLine(
20         "socket3 is {0}in writeList.",
21         writeList.Contains(socket3) ? "" : "not " );
22     Console.WriteLine(
23         "socket3 is {0}in errorList.",
24         errorList.Contains(socket3) ? "" : "not " );
25     }
26 }

```

27 The output is

```

28
29
30 socket3 is placed in readList and errorList.
31
32
33 socket3 is in readList.
34
35
36 socket3 is not in writeList.
37
38
39 socket3 is in errorList.
40
41
42 The Select method has been called.
43
44
45 socket3 is not in readList.
46
47
48 socket3 is not in writeList.
49
50
51 socket3 is not in errorList.
52

```

53

Socket.Send(System.Byte[], System.Int32, System.Int32, System.Net.Sockets.SocketFlags) Method

```
[ILAsm]
.method public hidebysig instance int32 Send(class System.Byte[] buffer,
int32 offset, int32 size, valuetype System.Net.Sockets.SocketFlags
socketFlags)

[C#]
public int Send(byte[] buffer, int offset, int size, SocketFlags
socketFlags)
```

Summary

Sends data to a connected socket.

Parameters

| Parameter | Description |
|--------------------|--|
| <i>buffer</i> | A System.Byte array containing data to send to the socket. |
| <i>offset</i> | A System.Int32 that specifies the zero-based position in buffer that is the starting location of the data to send. |
| <i>size</i> | A System.Int32 containing the number of bytes to send. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.DontRoute, or System.Net.Sockets.SocketFlags.OutOfBand. |

Return Value

A System.Int32 containing the number of bytes sent.

Description

For connection-oriented protocols, the System.Net.Sockets.Socket.LocalEndPoint property of the current instance is required to be set before calling this method.

For connectionless protocols, calling the System.Net.Sockets.Socket.Connect methods sets the System.Net.Sockets.Socket.RemoteEndPoint property and allows the System.Net.Sockets.Socket.Send method to be used instead of the

1 `System.Net.Sockets.Socket.SendTo` method.
 2
 3 When the `System.Net.Sockets.SocketFlags.DontRoute` flag is specified as part of the
 4 `socketFlags` parameter, the sent data is not routed.
 5
 6 When the `System.Net.Sockets.SocketFlags.OutOfBand` flag is specified as part of the
 7 `socketFlags` parameter, only out-of-band (OOB) data is sent.
 8
 9 When the `System.Net.Sockets.Socket.Blocking` property of the current instance is
 10 set to `true` and buffer space is not available within the underlying protocol, this method
 11 blocks.
 12
 13 For message-oriented sockets, when `size` is greater than the maximum message size of
 14 the underlying protocol, no data is sent and the `System.Net.Sockets.SocketException`
 15 exception is thrown.

16 **Exceptions**

| Exception | Condition |
|---|---|
| System.ArgumentNullException | <i>buffer</i> is null. |
| System.ArgumentOutOfRangeException | <i>offset</i> < 0. -or- <i>offset</i> > <i>buffer.Length</i> . -or- <i>size</i> < 0. -or- <i>size</i> > <i>buffer.Length</i> - <i>offset</i> . |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | <i>socketFlags</i> is not a valid combination of values. -or- An error occurred while accessing the socket. [Note: For additional information on causes of |

| | |
|---------------------------------------|---|
| | the SocketException, see the System.Net.Sockets.SocketException class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2

1 Socket.Send(System.Byte[]) Method

```
2 [ILAsm]  
3 .method public hidebysig instance int32 Send(class System.Byte[] buffer)  
4 [C#]  
5 public int Send(byte[] buffer)
```

6 Summary

7 Sends data to a connected socket.

8 Parameters

| Parameter | Description |
|---------------|--|
| <i>buffer</i> | A System.Byte array containing data to send to the socket. |

9 Return Value

11 A System.Int32 containing the number of bytes sent.

12 Description

13 This method is equivalent to System.Net.Sockets.Socket.Send(*buffer*, 0,
14 *buffer.Length*, System.Net.Sockets.SocketFlags.None).

15 Exceptions

| Exception | Condition |
|---|---|
| System.ArgumentNullException | <i>buffer</i> is null. |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [Note: For additional information on causes of the SocketException, see the System.Net.Sockets.SocketException class.] |

System.ObjectDisposedException

The current instance has been disposed.

1

2

1 Socket.Send(System.Byte[], 2 System.Net.Sockets.SocketFlags) Method

```
3 [ILAsm]  
4 .method public hidebysig instance int32 Send(class System.Byte[] buffer,  
5 valuetype System.Net.Sockets.SocketFlags socketFlags)  
  
6 [C#]  
7 public int Send(byte[] buffer, SocketFlags socketFlags)
```

8 Summary

9 Sends data to a connected socket.

10 Parameters

| Parameter | Description |
|--------------------|--|
| <i>buffer</i> | A System.Byte array containing data to send to the socket. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.DontRoute, OR System.Net.Sockets.SocketFlags.OutOfBand. |

11 12 Return Value

13 A System.Int32 containing the number of bytes sent.

14 Description

15 This method is equivalent to System.Net.Sockets.Socket.Send(*buffer*, 0,
16 *buffer.Length*, *socketFlags*).

17 Exceptions

| Exception | Condition |
|----------------------------------|--|
| System.ArgumentNullException | <i>buffer</i> is null. |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |

| | |
|---|---|
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.ObjectDisposedException | <p>The current instance has been disposed.</p> |

1

2

1 Socket.Send(System.Byte[], System.Int32, 2 System.Net.Sockets.SocketFlags) Method

```
3 [ILAsm]  
4 .method public hidebysig instance int32 Send(class System.Byte[] buffer,  
5 int32 size, valuetype System.Net.Sockets.SocketFlags socketFlags)  
  
6 [C#]  
7 public int Send(byte[] buffer, int size, SocketFlags socketFlags)
```

8 Summary

9 Sends data to a connected socket.

10 Parameters

| Parameter | Description |
|--------------------|--|
| <i>buffer</i> | A System.Byte array containing data to send to the socket. |
| <i>size</i> | A System.Int32 containing the number of bytes to send. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.DontRoute, or System.Net.Sockets.SocketFlags.OutOfBand. |

12 Return Value

13 A System.Int32 containing the number of bytes sent.

14 Description

15 This method is equivalent to System.Net.Sockets.Socket.Send(*buffer*, 0, *size*,
16 *socketFlags*).

17 Exceptions

| Exception | Condition |
|---|------------------------|
| System.ArgumentNullException | <i>buffer</i> is null. |
| System.ArgumentOutOfRangeException | <i>size</i> < 0. |

| | |
|---|---|
| | <p>-or-</p> <p><i>size</i> > <i>buffer.Length</i>.</p> |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2

1 Socket.SendTo(System.Byte[], 2 System.Net.EndPoint) Method

```
3 [ILAsm]  
4 .method public hidebysig instance int32 SendTo(class System.Byte[] buffer,  
5 class System.Net.EndPoint remoteEP)  
  
6 [C#]  
7 public int SendTo(byte[] buffer, EndPoint remoteEP)
```

8 Summary

9 Sends data to the socket associated with the specified endpoint.

10 Parameters

| Parameter | Description |
|-----------------|---|
| <i>buffer</i> | A System.Byte array containing data to send to the socket. |
| <i>remoteEP</i> | The System.Net.EndPoint associated with the socket to receive the data. |

11

12 Return Value

13 A System.Int32 containing the number of bytes sent.

14 Description

15 This method is equivalent to System.Net.Sockets.Socket.SendTo(*buffer*, 0,
16 *buffer.Length*, System.Net.Sockets.SocketFlags.None, *remoteEP*).

17 Exceptions

| Exception | Condition |
|---|---|
| System.ArgumentNullException | <i>buffer</i> or <i>remoteEP</i> is null. |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [Note: For additional information on causes of the SocketException, see the System.Net.Sockets.SocketException class.] |

| | |
|--|--|
| | |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to make a connection to the endpoint defined by <i>remoteEP</i> . See <code>System.Net.NetworkAccess.Connect</code> . |

3

4

1 Socket.SendTo(System.Byte[], 2 System.Net.Sockets.SocketFlags, 3 System.Net.EndPoint) Method

```
4 [ILAsm]  
5 .method public hidebysig instance int32 SendTo(class System.Byte[] buffer,  
6 valuetype System.Net.Sockets.SocketFlags socketFlags, class  
7 System.Net.EndPoint remoteEP)  
  
8 [C#]  
9 public int SendTo(byte[] buffer, SocketFlags socketFlags, EndPoint  
10 remoteEP)
```

11 Summary

12 Sends data to the socket associated with the specified endpoint.

13 Parameters

| Parameter | Description |
|--------------------|--|
| <i>buffer</i> | A System.Byte array containing data to send to the socket. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.DontRoute, or System.Net.Sockets.SocketFlags.OutOfBand. |
| <i>remoteEP</i> | The System.Net.EndPoint associated with the socket to receive the data. |

14 15 Return Value

16 A System.Int32 containing the number of bytes sent.

17 Description

18 This method is equivalent to System.Net.Sockets.Socket.SendTo(*buffer*, 0,
19 *buffer.Length*, *socketFlags*, *remoteEP*).

20 Exceptions

| Exception | Condition |
|-----------|-----------|
|-----------|-----------|

| | |
|---|---|
| System.ArgumentNullException | <i>buffer</i> or <i>remoteEP</i> is null. |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to make a connection to the endpoint defined by <i>remoteEP</i> . See <code>System.Net.NetworkAccess.Connect</code> . |

3

4

1 Socket.SendTo(System.Byte[], System.Int32, 2 System.Net.Sockets.SocketFlags, 3 System.Net.EndPoint) Method

```
4 [ILAsm]  
5 .method public hidebysig instance int32 SendTo(class System.Byte[] buffer,  
6 int32 size, valuetype System.Net.Sockets.SocketFlags socketFlags, class  
7 System.Net.EndPoint remoteEP)  
  
8 [C#]  
9 public int SendTo(byte[] buffer, int size, SocketFlags socketFlags,  
10 EndPoint remoteEP)
```

11 Summary

12 Sends data to the socket associated with the specified endpoint.

13 Parameters

| Parameter | Description |
|--------------------|--|
| <i>buffer</i> | A System.Byte array containing data to send to the socket. |
| <i>size</i> | A System.Int32 containing the number of bytes to send. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.DontRoute, or System.Net.Sockets.SocketFlags.OutOfBand. |
| <i>remoteEP</i> | The System.Net.EndPoint associated with the socket to receive the data. |

14 15 Return Value

16 A System.Int32 containing the number of bytes sent.

17 Description

18 This method is equivalent to System.Net.Sockets.Socket.SendTo(*buffer*, 0, *size*,
19 *socketFlags*, *remoteEP*).

20 Exceptions

| Exception | Condition |
|---|--|
| System.ArgumentNullException | <i>buffer</i> or <i>remoteEP</i> is null. |
| System.ArgumentOutOfRangeException | <i>size</i> < 0. -or- <i>size</i> > <i>buffer.Length</i> . |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |
| System.Net.Sockets.SocketException | <i>socketFlags</i> is not a valid combination of values. -or- An error occurred while accessing the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 Permissions

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to make a connection to the endpoint defined by <i>remoteEP</i> . See <code>System.Net.NetworkAccess.Connect</code> . |

3

4

1 Socket.SendTo(System.Byte[], System.Int32, 2 System.Int32, 3 System.Net.Sockets.SocketFlags, 4 System.Net.EndPoint) Method

```
5 [ILAsm]  
6 .method public hidebysig instance int32 SendTo(class System.Byte[] buffer,  
7 int32 offset, int32 size, valuetype System.Net.Sockets.SocketFlags  
8 socketFlags, class System.Net.EndPoint remoteEP)  
  
9 [C#]  
10 public int SendTo(byte[] buffer, int offset, int size, SocketFlags  
11 socketFlags, EndPoint remoteEP)
```

12 Summary

13 Sends data to the socket associated with the specified endpoint.

14 Parameters

| Parameter | Description |
|--------------------|--|
| <i>buffer</i> | A System.Byte array containing data to send to the socket. |
| <i>offset</i> | A System.Int32 that specifies the zero-based position in buffer that is the starting location of the data to send. |
| <i>size</i> | A System.Int32 containing the number of bytes to send. |
| <i>socketFlags</i> | A bitwise combination of any of the following values defined in the System.Net.Sockets.SocketFlags enumeration: System.Net.Sockets.SocketFlags.None, System.Net.Sockets.SocketFlags.DontRoute, or System.Net.Sockets.SocketFlags.OutOfBand. |
| <i>remoteEP</i> | The System.Net.EndPoint associated with the socket to receive the data. |

15 16 Return Value

17 A System.Int32 containing the number of bytes sent.

18 Description

1 For connected sockets using connectionless protocols, *remoteEP* overrides the endpoint
 2 specified in the `System.Net.Sockets.Socket.RemoteEndPoint` property.
 3
 4 For unconnected sockets using connectionless protocols, this method sets the
 5 `System.Net.Sockets.Socket.LocalEndPoint` property of the current instance to a
 6 value determined by the protocol. Subsequent data is required to be received on
 7 `LocalEndPoint`.
 8
 9 When the `System.Net.Sockets.SocketFlags.DontRoute` flag is specified as part of the
 10 *socketFlags* parameter, the sent data is not routed.
 11
 12 When the `System.Net.Sockets.SocketFlags.OutOfBand` flag is specified as part of the
 13 *socketFlags* parameter, only out-of-band (OOB) data is sent.
 14
 15 When the `System.Net.Sockets.Socket.Blocking` property of the current instance is
 16 set to `true` and buffer space is not available within the underlying protocol, this method
 17 blocks.
 18
 19 For message-oriented sockets, when *size* is greater than the maximum message size of
 20 the underlying protocol, no data is sent and the `System.Net.Sockets.SocketException`
 21 exception is thrown.
 22
 23 For connection-oriented sockets, the *remoteEP* parameter is ignored.

24 **Exceptions**

| Exception | Condition |
|---|--|
| System.ArgumentNullException | <i>buffer</i> or <i>remoteEP</i> is null. |
| System.ArgumentOutOfRangeException | <i>offset</i> < 0. -or- <i>offset</i> > <i>buffer.Length</i> . -or- <i>size</i> < 0. -or- <i>size</i> > <i>buffer.Length</i> - <i>offset</i> . |
| System.InvalidOperationException | An asynchronous call is pending and a blocking method has been called. |

| | |
|---|---|
| System.Net.Sockets.SocketException | <p><i>socketFlags</i> is not a valid combination of values.</p> <p>-or-</p> <p>An error occurred while accessing the socket.</p> <p>[<i>Note:</i> For additional information on causes of the <code>SocketException</code>, see the <code>System.Net.Sockets.SocketException</code> class.]</p> |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2 **Permissions**

| Permission | Description |
|------------------------------------|---|
| System.Net.SocketPermission | Requires permission to make a connection to the endpoint defined by <i>remoteEP</i> . See <code>System.Net.NetworkAccess.Connect</code> . |

3

4

1
2 **Socket.SetSocketOption(System.Net.Sockets.**
3 **SocketOptionLevel,**
4 **System.Net.Sockets.SocketOptionName,**
5 **System.Object) Method**

```
6 [ILAsm]
7 .method public hidebysig instance void SetSocketOption(valuetype
8 System.Net.Sockets.SocketOptionLevel optionLevel, valuetype
9 System.Net.Sockets.SocketOptionName optionName, object optionValue)

10 [C#]
11 public void SetSocketOption(SocketOptionLevel optionLevel,
12 SocketOptionName optionName, object optionValue)
```

13 **Summary**

14 Sets the System.Net.Sockets.SocketOptionName.AddMembership,
15 System.Net.Sockets.SocketOptionName.DropMembership, or
16 System.Net.Sockets.SocketOptionName.Linger socket options.

17 **Parameters**

| Parameter | Description |
|--------------------|--|
| <i>optionLevel</i> | Either the Socket or IP member of the System.Net.Sockets.SocketOptionLevel enumeration. |
| <i>optionName</i> | Either the Linger, AddMembership, or DropMembership member of the System.Net.Sockets.SocketOptionName enumeration. |
| <i>optionValue</i> | An instance of the System.Net.Sockets.LingerOption or System.Net.Sockets.MulticastOption class. |

18
19 **Description**

20 Socket options determine the behavior of the current instance. Multiple options can be
21 set on the current instance by calling this method multiple times.

22
23 The following table summarizes the valid combinations of input parameters.

| optionLevel/optionName | optionValue |
|------------------------|---|
| Socket/Linger | An instance of the System.Net.Sockets.LingerOption class. |

| | |
|-------------------|---|
| IP/AddMembership | An instance of the <code>System.Net.Sockets.MulticastOption</code> class. |
| - or - | |
| IP/DropMembership | |

1
2 When setting the `System.Net.Sockets.SocketOptionName.Linger` option, a
3 `System.ArgumentException` exception is thrown if the
4 `System.Net.Sockets.LingerOption.LingerTime` property of the
5 `System.Net.Sockets.LingerOption` instance is less than zero or greater than
6 `System.UInt16.MaxValue`.
7
8 [*Note:* For more information on the `System.Net.Sockets.SocketOptionName.Linger`
9 option, see the `System.Net.Sockets.LingerOption` class and the
10 `System.Net.Sockets.Socket.Shutdown` method.
11
12 For more information on the `System.Net.Sockets.SocketOptionName.AddMembership`
13 and `System.Net.Sockets.SocketOptionName.DropMembership` options, see the
14 `System.Net.Sockets.MulticastOption` class.
15
16 For socket options with values of type `System.Int32` or `System.Boolean`, see the
17 `System.Net.Sockets.Socket.SetSocketOption(System.Net.Sockets.SocketOptionLe`
18 `vel, System.Net.Sockets.SocketOptionName, System.Int32)` version of this method.
19
20]

21 **Exceptions**

| Exception | Condition |
|---|--|
| System.ArgumentException | <i>optionLevel</i> , <i>optionName</i> , or <i>optionValue</i> specified an invalid value. |
| System.ArgumentNullException | <i>optionValue</i> is null. |
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |

System.ObjectDisposedException

The current instance has been disposed.

1

2 **Permissions**

| Permission | Description |
|---|---|
| System.Security.Permissions.SecurityPermission | The <code>System.Net.Sockets.SocketOptionName.AddMembership</code> and <code>System.Net.Sockets.SocketOptionName.DropMembership</code> options require permission to access unmanaged code. See <code>System.Security.Permissions.SecurityPermissionFlag.UnmanagedCode</code> . |

3

4

1
2 **Socket.SetSocketOption(System.Net.Sockets.**
3 **SocketOptionLevel,**
4 **System.Net.Sockets.SocketOptionName,**
5 **System.Byte[]) Method**

```
6 [ILAsm]  
7 .method public hidebysig instance void SetSocketOption(valuetype  
8 System.Net.Sockets.SocketOptionLevel optionLevel, valuetype  
9 System.Net.Sockets.SocketOptionName optionName, class System.Byte[]  
10 optionValue)  
  
11 [C#]  
12 public void SetSocketOption(SocketOptionLevel optionLevel,  
13 SocketOptionName optionName, byte[] optionValue)
```

14 **Summary**

15 Sets socket options with values of type Byte [] .

16 **Parameters**

| Parameter | Description |
|--------------------|--|
| <i>optionLevel</i> | One of the values defined in the System.Net.Sockets.SocketOptionLevel enumeration. |
| <i>optionName</i> | One of the values defined in the System.Net.Sockets.SocketOptionName enumeration. |
| <i>optionValue</i> | A System.Byte array containing the value of the option. |

17
18 **Description**

19 Socket options determine the behavior of the current instance. Multiple options can be
20 set on the current instance by calling this method multiple times.

21
22 [Note: For socket options with values of type System.Int32 or System.Boolean, see the
23 System.Net.Sockets.Socket.SetSocketOption(System.Net.Sockets.SocketOptionLe
24 vel, System.Net.Sockets.SocketOptionName, System.Int32) version of this method.]

25
26
27
28 [Note: For the System.Net.Sockets.SocketOptionName.AddMembership,
29 System.Net.Sockets.SocketOptionName.DropMembership, or
30 System.Net.Sockets.SocketOptionName.Linger socket options, see the

1 `System.Net.Sockets.Socket.SetSocketOption(System.Net.Sockets.SocketOptionLe`
2 `vel, System.Net.Sockets.SocketOptionName, System.Object)` version of this
3 `method.`
4
5

6 Exceptions

| Exception | Condition |
|---|--|
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

7

8 Permissions

| Permission | Description |
|---|---|
| System.Security.Permissions.SecurityPermission | Requires permission to access unmanaged code. See <code>System.Security.Permissions.SecurityPermissionFlag.UnmanagedCode</code> . |

9

10

1
2 **Socket.SetSocketOption(System.Net.Sockets.**
3 **SocketOptionLevel,**
4 **System.Net.Sockets.SocketOptionName,**
5 **System.Int32) Method**

```
6 [ILAsm]  
7 .method public hidebysig instance void SetSocketOption(valuetype  
8 System.Net.Sockets.SocketOptionLevel optionLevel, valuetype  
9 System.Net.Sockets.SocketOptionName optionName, int32 optionValue)  
  
10 [C#]  
11 public void SetSocketOption(SocketOptionLevel optionLevel,  
12 SocketOptionName optionName, int optionValue)
```

13 **Summary**

14 Sets socket options with values of type System.Int32 and System.Boolean.

15 **Parameters**

| Parameter | Description |
|--------------------|--|
| <i>optionLevel</i> | One of the values defined in the System.Net.Sockets.SocketOptionLevel enumeration. |
| <i>optionName</i> | One of the values defined in the System.Net.Sockets.SocketOptionName enumeration. |
| <i>optionValue</i> | A System.Int32 containing the value of the option. |

16
17 **Description**

18 Socket options determine the behavior of the current instance. Multiple options can be
19 set on the current instance by calling this method multiple times.

20
21 For a socket option with a System.Boolean data type, specify a non-zero *optionValue* to
22 enable the option, and an *optionValue* equal to zero to disable the option.

23
24 Socket options are grouped by level of protocol support. The following tables list the
25 members of the System.Net.Sockets.SocketOptionName enumeration supported by
26 each member of the System.Net.Sockets.SocketOptionLevel enumeration. Only
27 members that have associated values of the System.Int32 and System.Boolean data
28 types are listed.
29

1 The following table lists the members of the `System.Net.Sockets.SocketOptionName`
 2 enumeration supported by the `Socket` member of the
 3 `System.Net.Sockets.SocketOptionLevel` enumeration. Options that do not require
 4 permission to access unmanaged code are noted.

| SocketOptionName | Description |
|------------------|--|
| Broadcast | A <code>System.Boolean</code> where <code>true</code> indicates broadcast messages are allowed to be sent to the socket. |
| Debug | A <code>System.Boolean</code> where <code>true</code> indicates to record debugging information. |
| DontLinger | A <code>System.Boolean</code> where <code>true</code> indicates to close the socket without lingering. This option does not require permission to access unmanaged code. |
| DontRoute | A <code>System.Boolean</code> where <code>true</code> indicates not to route data. |
| Error | A <code>System.Int32</code> that contains the error code associated with the last socket error. The error code is cleared by this option. This option is read-only. |
| KeepAlive | A <code>System.Boolean</code> where <code>true</code> (the default) indicates to enable keep-alives, which allows a connection to remain open after a request has completed. This option does not require permission to access unmanaged code. |
| OutOfBandInline | A <code>System.Boolean</code> where <code>true</code> indicates to receive out-of-band data in the normal data stream. |
| ReceiveBuffer | A <code>System.Int32</code> that specifies the total per-socket buffer space reserved for receives. This option does not require permission to access unmanaged code. |
| ReceiveTimeout | A <code>System.Int32</code> that specifies the maximum time, in milliseconds, the <code>System.Net.Sockets.Socket.Receive</code> and <code>System.Net.Sockets.Socket.ReceiveFrom</code> methods will block when attempting to receive data. If data is not received within this time, a <code>System.Net.Sockets.SocketException</code> exception is thrown. This option does not require permission to access unmanaged code. |
| ReuseAddress | A <code>System.Boolean</code> where <code>true</code> allows the socket to be bound to an address that is already in use. |

| | |
|-------------|---|
| SendBuffer | A <code>System.Int32</code> that specifies the total per-socket buffer space reserved for sends. This option does not require permission to access unmanaged code. |
| SendTimeout | A <code>System.Int32</code> that specifies the maximum time, in milliseconds, the <code>System.Net.Sockets.Socket.Send</code> and <code>System.Net.Sockets.Socket.SendTo</code> methods will block when attempting to send data. If data is not sent within this time, a <code>System.Net.Sockets.SocketException</code> exception is thrown. This option does not require permission to access unmanaged code. |
| Type | One of the values defined in the <code>System.Net.Sockets.SocketType</code> enumeration. This option is read-only. |

1
2 The following table lists the members of the `System.Net.Sockets.SocketOptionName`
3 enumeration supported by the IP member of the
4 `System.Net.Sockets.SocketOptionLevel` enumeration. These options require
5 permission to access unmanaged code.

| SocketOptionName | Description |
|---------------------|--|
| HeaderIncluded | A <code>System.Boolean</code> where <code>true</code> indicates the application is providing the IP header for outgoing datagrams. |
| IPOptions | A <code>System.Byte</code> array that specifies IP options to be inserted into outgoing datagrams. |
| IpTimeToLive | A <code>System.Int32</code> that specifies the time-to-live for datagrams. The time-to-live designates the number of networks on which the datagram is allowed to travel before being discarded by a router. |
| MulticastInterface | A <code>System.Byte</code> array that specifies the interface for outgoing multicast packets. |
| MulticastLoopback | A <code>System.Boolean</code> where <code>true</code> enables multicast loopback. |
| MulticastTimeToLive | A <code>System.Int32</code> that specifies the time-to-live for multicast datagrams. |
| TypeOfService | A <code>System.Int32</code> that specifies the type of service field in the IP header. |
| UseLoopback | A <code>System.Boolean</code> where <code>true</code> indicates to send a copy of the data |

| | |
|--|---------------------|
| | back to the sender. |
|--|---------------------|

1
2
3
4
5
6
7

The following table lists the members of the `System.Net.Sockets.SocketOptionName` enumeration supported by the `Tcp` member of the `System.Net.Sockets.SocketOptionLevel` enumeration. These options do not require permission to access unmanaged code.

| SocketOptionName | Description |
|------------------|--|
| BsdUrgent | A <code>System.Boolean</code> where <code>true</code> indicates to use urgent data as defined by IETF RFC 1222. Once enabled, this option cannot be disabled. |
| Expedited | A <code>System.Boolean</code> where <code>true</code> indicates to use expedited data as defined by IETF RFC 1222. Once enabled, this option cannot be disabled. |
| NoDelay | A <code>System.Boolean</code> where <code>true</code> indicates to disable the Nagle algorithm for send coalescing. |

8
9
10
11
12
13
14

The following table lists the members of the `System.Net.Sockets.SocketOptionName` enumeration supported by the `Udp` member of the `System.Net.Sockets.SocketOptionLevel` enumeration. These options do not require permission to access unmanaged code.

| SocketOptionName | Description |
|------------------|--|
| ChecksumCoverage | A <code>System.Boolean</code> that specifies UDP checksum coverage. |
| NoChecksum | A <code>System.Boolean</code> where <code>true</code> indicates to send UDP datagrams with the checksum set to zero. |

15
16
17
18
19
20
21

[Note: For the `AddMembership`, `DropMembership`, and `Linger` members of the `System.Net.Sockets.SocketOptionName` enumeration, see the `System.Net.Sockets.Socket.SetSocketOption(System.Net.Sockets.SocketOptionLevel, System.Net.Sockets.SocketOptionName, System.Object)` version of this method.

1
2]

3 Exceptions

| Exception | Condition |
|---|--|
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.Security.SecurityException | A caller in the call stack does not have the required permissions. |
| System.ObjectDisposedException | The current instance has been disposed. |

4 5 Permissions

| Permission | Description |
|---|--|
| System.Security.Permissions.SecurityPermission | Some options require permission to access unmanaged code. All the options that do not require permission are noted in the tables in the Description section. All options not so noted require this permission. See <code>System.Security.Permissions.SecurityPermissionFlag.UnmanagedCode</code> . |

6
7

Socket.Shutdown(System.Net.Sockets.Socket Shutdown) Method

```
[ILAsm]
.method public hidebysig instance void Shutdown(valuetype
System.Net.Sockets.SocketShutdown how)

[C#]
public void Shutdown(SocketShutdown how)
```

Summary

Terminates the ability to send or receive data on a connected socket.

Parameters

| Parameter | Description |
|------------|--|
| <i>how</i> | One of the values defined in the <code>System.Net.Sockets.SocketShutdown</code> enumeration. |

Description

When *how* is set to `System.Net.Sockets.SocketShutdown.Send`, the socket on the other end of the connection is notified that the current instance will not send any more data. If the `System.Net.Sockets.Socket.Send` method is subsequently called, a `System.Net.Sockets.SocketException` exception is thrown.

When *how* is set to `System.Net.Sockets.SocketShutdown.Receive`, the socket on the other end of the connection is notified that the current instance will not receive any more data. After all the data currently queued on the current instance is received, any subsequent calls to the `System.Net.Sockets.Socket.Receive` method cause a `System.Net.Sockets.SocketException` exception to be thrown.

Setting *how* to `System.Net.Sockets.SocketShutdown.Both` terminates both sends and receives as described above. Once this occurs, the socket cannot be used.

[*Note:* To free resources allocated by the current instance, call the `System.Net.Sockets.Socket.Close` method.

Expected common usage is for the `System.Net.Sockets.Socket.Shutdown` method to be called before the `System.Net.Sockets.Socket.Close` method to ensure that all pending data is sent or received.

]

Exceptions

| Exception | Condition |
|---|--|
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

1

2

1 Socket.System.IDisposable.Dispose() Method

```
2 [ILAsm]  
3 .method private final hidebysig virtual void System.IDisposable.Dispose()  
4 [C#]  
5 void IDisposable.Dispose()
```

6 Summary

7 Implemented to support the System.IDisposable interface. [Note: For more
8 information, see System.IDisposable.Dispose.]

9

1 Socket.AddressFamily Property

```
2 [ILAsm]  
3 .property valuetype System.Net.Sockets.AddressFamily AddressFamily {  
4 public hidebysig specialname instance valuetype  
5 System.Net.Sockets.AddressFamily get_AddressFamily() }  
  
6 [C#]  
7 public AddressFamily AddressFamily { get; }
```

8 Summary

9 Gets the address family of the current instance.

10 Property Value

11 One of the values defined in the `System.Net.Sockets.AddressFamily` enumeration.

12 Description

13 This property is read-only.

14
15 This property is set by the constructor for the current instance. The value of this
16 property specifies the addressing scheme used by the current instance to resolve an
17 address.

18

1 Socket.Available Property

```
2 [ILAsm]  
3 .property int32 Available { public hidebysig specialname instance int32  
4 get_Available() }  
  
5 [C#]  
6 public int Available { get; }
```

7 Summary

8 Gets the amount of data available to be read in a single
9 System.Net.Sockets.Socket.Receive OR System.Net.Sockets.Socket.ReceiveFrom
10 call.

11 Property Value

12 A System.Int32 containing the number of bytes of data that are available to be read.

13 Description

14 This property is read-only.

15
16 When the current instance is stream-oriented (for example, the
17 System.Net.Sockets.SocketType.Stream socket type), the available data is generally
18 the total amount of data queued on the current instance.

19
20 When the current instance is message-oriented (for example, the
21 System.Net.Sockets.SocketType.Dgram socket type), the available data is the first
22 message in the input queue.

23 Exceptions

| Exception | Condition |
|---|---|
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [Note: For additional information on causes of the SocketException, see the System.Net.Sockets.SocketException class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

24

25

1 Socket.Blocking Property

```
2 [ILAsm]
3 .property bool Blocking { public hidebysig specialname instance bool
4 get_Blocking() public hidebysig specialname instance void
5 set_Blocking(bool value) }
6 [C#]
7 public bool Blocking { get; set; }
```

8 Summary

9 Gets or sets a `System.Boolean` value that indicates whether the socket is in blocking
10 mode.

11 Property Value

12 `true` indicates that the current instance is in blocking mode; `false` indicates that the
13 current instance is in non-blocking mode.

14 Description

15 Blocking is when a method waits to complete an operation before returning. Sockets are
16 created in blocking mode by default.

17 Exceptions

| Exception | Condition |
|---------------------------------------|---|
| System.ObjectDisposedException | The current instance has been disposed. |

18

19

1 Socket.Connected Property

```
2 [ILAsm]  
3 .property bool Connected { public hidebysig specialname instance bool  
4 get_Connected() }  
5 [C#]  
6 public bool Connected { get; }
```

7 Summary

8 Gets a `System.Boolean` value indicating whether the current instance is connected.

9 Property Value

10 `true` indicates that the current instance was connected at the time of the last I/O
11 operation; `false` indicates that the current instance is not connected.

12 Description

13 This property is read-only.

14
15 When this property returns `true`, the current instance was connected at the time of the
16 last I/O operation; it might not still be connected. When this property returns `false`, the
17 current instance was never connected or is not currently connected.

18
19 The current instance is considered connected when the
20 `System.Net.Sockets.Socket.RemoteEndPoint` property contains a valid endpoint.

21
22 [*Note:* The `System.Net.Sockets.Socket.Accept` and
23 `System.Net.Sockets.Socket.Connect` methods, and their asynchronous counterparts
24 set this property.]
25
26

27

1 **The following member must be implemented if the RuntimeInfrastructure library is**
2 **present in the implementation.**

3 Socket.Handle Property

```
4 [ILAsm]  
5 .property valuetype System.IntPtr Handle { public hidebysig specialname  
6 instance valuetype System.IntPtr get_Handle() }  
7 [C#]  
8 public IntPtr Handle { get; }
```

9 Summary

10 Gets the operating system handle for the current instance.

11 Property Value

12 A System.IntPtr containing the operating system handle for the current instance.

13 Description

14 This property is read-only.

15 Permissions

| Permission | Description |
|---|---|
| System.Security.Permissions.SecurityPermission | Requires permission to access unmanaged code. See System.Security.Permissions.SecurityPermissionFlag.UnmanagedCode. |

16

17

1 Socket.LocalEndPoint Property

```
2 [ILAsm]  
3 .property class System.Net.EndPoint LocalEndPoint { public hidebysig  
4 specialname instance class System.Net.EndPoint get_LocalEndPoint() }  
5 [C#]  
6 public EndPoint LocalEndPoint { get; }
```

7 Summary

8 Gets the local endpoint associated with the current instance.

9 Property Value

10 The local `System.Net.EndPoint` associated with the current instance.

11 Description

12 This property is read-only.

13 This property contains the network connection information for the current instance.

14
15
16 [Note: The `System.Net.Sockets.Socket.Bind` and
17 `System.Net.Sockets.Socket.Accept` methods, and their asynchronous counterparts
18 set this property. If not previously set, the `System.Net.Sockets.Socket.Connect` and
19 `System.Net.Sockets.Socket.SendTo` methods, and their asynchronous counterparts
20 set this property.]
21
22

23 Exceptions

| Exception | Condition |
|---|--|
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [Note: For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

24

25

1 Socket.ProtocolType Property

```
2 [ILAsm]  
3 .property valuetype System.Net.Sockets.ProtocolType ProtocolType { public  
4 hidebysig specialname instance valuetype System.Net.Sockets.ProtocolType  
5 get_ProtocolType() }  
6 [C#]  
7 public ProtocolType ProtocolType { get; }
```

8 Summary

9 Gets the protocol type of the current instance.

10 Property Value

11 One of the values defined in the `System.Net.Sockets.ProtocolType` enumeration.

12 Description

13 This property is read-only.

14

15 This property is set by the constructor for the current instance. The value of this
16 property specifies the protocol used by the current instance.

17

1 Socket.RemoteEndPoint Property

```
2 [ILAsm]  
3 .property class System.Net.EndPoint RemoteEndPoint { public hideby sig  
4 specialname instance class System.Net.EndPoint get_RemoteEndPoint() }  
  
5 [C#]  
6 public EndPoint RemoteEndPoint { get; }
```

7 Summary

8 Gets the remote endpoint associated with the current instance.

9 Property Value

10 The remote `System.Net.EndPoint` associated with the current instance.

11 Description

12 This property is read-only.

13
14 This property contains the network connection information associated with the socket
15 communicating with the current instance.

16
17 There is no remote endpoint associated with a socket in the listening state. An attempt
18 to access the `System.Net.Sockets.Socket.RemoteEndPoint` property causes a
19 `System.Net.Sockets.SocketException` exception to be thrown.

20
21 [*Note:* The `System.Net.Sockets.Socket.Accept` and
22 `System.Net.Sockets.Socket.Connect` methods, and their asynchronous counterparts
23 set this property.]

26 Exceptions

| Exception | Condition |
|---|--|
| System.Net.Sockets.SocketException | An error occurred while accessing the socket. [<i>Note:</i> For additional information on causes of the <code>SocketException</code> , see the <code>System.Net.Sockets.SocketException</code> class.] |
| System.ObjectDisposedException | The current instance has been disposed. |

27

28

1 Socket.SocketType Property

```
2 [ILAsm]  
3 .property valuetype System.Net.Sockets.SocketType SocketType { public  
4 hidebysig specialname instance valuetype System.Net.Sockets.SocketType  
5 get_SocketType() }  
6 [C#]  
7 public SocketType SocketType { get; }
```

8 Summary

9 Gets the socket type of the current instance.

10 Property Value

11 One of the values defined in the `System.Net.Sockets.SocketType` enumeration.

12 Description

13 This property is read-only.

14

15 This property is set by the constructor for the current instance.

16