

# System.Double Structure

```
[ILAsm]
.class public sequential sealed serializable Double extends
System.ValueType implements System.IComparable, System.IFormattable,
System.IComparable`1<float64>, System.IEquatable`1<float64>

[C#]
public struct Double: IComparable, IFormattable, IComparable<Double>,
IEquatable<Double>
```

## Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- *Version:* 2.0.x.x
- *Attributes:*
  - CLSCompliantAttribute(true)

## Implements:

- **System.IComparable**
- **System.IFormattable**
- **System.IComparable<System.Double>**
- **System.IEquatable<System.Double>**

## Summary

Represents a 64-bit double-precision floating-point number.

## Inherits From: System.ValueType

**Library:** ExtendedNumerics

**Thread Safety:** This type is not guaranteed to be safe for multithreaded operations.

## Description

`System.Double` is a 64-bit double precision floating-point type that represents values ranging from approximately  $5.0E-324$  to  $1.7E+308$  and from approximately  $-5.0E-324$  to  $-1.7E+308$  with a precision of 15-16 decimal digits. The `System.Double` type conforms to IEEE Standard 754-2008 Floating-point Arithmetic.

A `System.Double` can represent the following values:

- The finite set of non-zero values of the form  $s * m * 2^e$ , where  $s$  is 1 or -1, and  $0 < m < 2^{53}$  and  $-1075 \leq e \leq 970$ .

- Positive and negative zero. The two zeroes are equal, so it holds that  $+0.0 == -0.0$ , and they behave identically with respect to all comparisons. However, they produce different results in some operations. For instance,  $1/+0.0$  gives `System.Double.PositiveInfinity`, whereas  $1/-0.0$  gives `System.Double.NegativeInfinity`.
- Positive infinity and negative infinity. Infinities are produced by operations that produce results with a magnitude greater than that which can be represented by a `System.Double`, such as dividing a non-zero number by zero. For example, using `System.Double` operands,  $1.0 / 0.0$  yields positive infinity, and  $-1.0 / 0.0$  yields negative infinity. Operations include passing parameters and returning values.
- The *Not-a-Number* values (NaN). NaN values are produced by invalid floating-point operations, such as dividing zero by zero.

When performing binary operations, if one of the operands is a `System.Double`, then the other operand is required to be an integral type or a floating-point type (`System.Double` or `System.Single`). Prior to performing the operation, if the other operand is not a `System.Double`, it is converted to `System.Double`, and the operation is performed using at least `System.Double` range and precision. If the operation produces a numeric result, the type of the result is `System.Double`.

The floating-point operators, including the assignment operators, do not throw exceptions. Instead, in exceptional situations, the result of a floating-point operation is zero, infinity, or NaN, as described below:

- If the result of a floating-point operation is too small for the destination format, the result of the operation is zero.
- If the magnitude of the result of a floating-point operation is too large for the destination format, the result of the operation is positive infinity or negative infinity, as appropriate for the sign of the result.
- If a floating-point operation is invalid, the result of the operation is a NaN.
- If one or both operands of a floating-point operation are NaN, the result of the operation is a NaN, which must preserve the payload (error bits) of one of the operand NaNs; see IEEE Standard 754-2008 Floating Point Arithmetic, section 6.2.1.

Conforming implementations of the CLI are permitted to perform floating-point operations using a precision that is higher than that required by the `System.Double` type. For example, hardware architectures that support an "extended" or "long double" floating-point type with greater range and precision than the `System.Double` type could implicitly perform all floating-point operations using this higher precision type. Expressions evaluated using a higher precision might cause a finite result to be produced instead of an infinity.

# Double.Epsilon Field

```
[ILAsm]  
.field public static literal float64 Epsilon = 4.9406564584124654e-324  
  
[C#]  
public const double Epsilon = 4.9406564584124654e-324
```

## Summary

Represents the smallest positive `System.Double` value greater than zero.

## Description

The value of this constant is 4.9406564584124654E-324.

# Double.MaxValue Field

```
[ILAsm]  
.field public static literal float64 MaxValue = 1.7976931348623157e+308  
  
[C#]  
public const double MaxValue = 1.7976931348623157e+308
```

## Summary

Contains the maximum positive value for the `System.Double` type.

## Description

The value of this constant is 1.7976931348623157E+308.

# Double.MinValue Field

```
[ILAsm]  
.field public static literal float64 MinValue = -1.7976931348623157e+308  
  
[C#]  
public const double MinValue = -1.7976931348623157e+308
```

## Summary

Contains the minimum (most negative) value for the `System.Double` type.

## Description

The value of this constant is -1.7976931348623157E+308.

# Double.NaN Field

```
[ILAsm]  
.field public static literal float64 NaN = (double)0.0 / (double)0.0  
  
[C#]  
public const double NaN = (double)0.0 / (double)0.0
```

## Summary

Represents an undefined result of operations involving `System.Double`.

## Description

Not-a-Number (NaN) values are returned when the result of a `System.Double` operation is undefined.

A NaN value is not equal to any other value, including another NaN value.

The value of this field is obtained by dividing `System.Double` zero by zero.

[*Note:* `System.Double.NaN` represents one of many possible NaN values. To test whether a `System.Double` value is a NaN, use the `System.Double.IsNaN` method.]

# Double.NegativeInfinity Field

```
[ILAsm]  
.field public static literal float64 NegativeInfinity = (double)-1.0 /  
(double)(0.0)
```

```
[C#]  
public const double NegativeInfinity = (double)-1.0 / (double)(0.0)
```

## Summary

Represents a negative infinity of type `System.Double`.

## Description

The value of this constant is obtained by dividing a negative `System.Double` by zero.

[*Note:* To test whether a `System.Double` value is a negative infinity value, use the `System.Double.IsNegativeInfinity` method.]

# Double.PositiveInfinity Field

```
[ILAsm]  
.field public static literal float64 PositiveInfinity = (double)1.0 /  
(double)(0.0)
```

```
[C#]  
public const double PositiveInfinity = (double)1.0 / (double)(0.0)
```

## Summary

Represents a positive infinity of type `System.Double`.

## Description

The value of this constant is obtained by dividing a positive `System.Double` by zero.

[*Note:* To test whether a `System.Double` value is a positive infinity value, use the `System.Double.IsPositiveInfinity` method.]



# Double.CompareTo(System.Double) Method

```
[ILAsm]  
.method public final hidebysig virtual int32 CompareTo(float64 value)  
  
[C#]  
public int CompareTo(double value)
```

## Summary

Returns the sort order of the current instance compared to the specified `System.Double`.

## Parameters

| Parameter    | Description  |
|--------------|--|
| <i>value</i> | The <code>System.Double</code> to compare to the current instance. |

## Return Value

The return value is a negative number, zero, or a positive number reflecting the sort order of the current instance as compared to *value*. For non-zero return values, the exact value returned by this method is unspecified. The following table defines the return value:

| Value               | Description  |
|---------------------|--|
| Any negative number | Current instance < <i>value</i> .<br><br>-or-<br><br>Current instance is a NaN and <i>value</i> is not a NaN.                                  |
| Zero                | Current instance == <i>value</i> .<br><br>-or-<br><br>Current instance and <i>value</i> are both NaN, positive infinity, or negative infinity. |
| A positive number   | Current instance > <i>value</i> .<br><br>-or-  |

|  |  |
|--|--|
|  | Current instance is not a NaN and <i>value</i> is a NaN. |
|--|--|

1

## 2 **Description**

3     [*Note:* This method is implemented to support the `System.IComparable<Double>`  
4     interface.]

5

6

7

# Double.CompareTo(System.Object) Method

```
[ILAsm]  
.method public final hidebysig virtual int32 CompareTo(object value)  
  
[C#]  
public int CompareTo(object value)
```

## Summary

Returns the sort order of the current instance compared to the specified `System.Object`.

## Parameters

| Parameter    | Description  |
|--------------|--|
| <i>value</i> | The <code>System.Object</code> to compare to the current instance. |

## Return Value

The return value is a negative number, zero, or a positive number reflecting the sort order of the current instance as compared to *value*. For non-zero return values, the exact value returned by this method is unspecified. The following table defines the return value:

| Value               | Description  |
|---------------------|--|
| Any negative number | Current instance < <i>value</i> .<br><br>-or-<br><br>Current instance is a NaN and <i>value</i> is not a NaN and is not a null reference.      |
| Zero                | Current instance == <i>value</i> .<br><br>-or-<br><br>Current instance and <i>value</i> are both NaN, positive infinity, or negative infinity. |
| A positive number   | Current instance > <i>value</i> .<br><br>-or-  |

|  |  |
|--|--|
|  | <p><i>value</i> is a null reference.</p> <p>-or-</p> <p>Current instance is not a NaN and <i>value</i> is a NaN.</p> |
|--|--|

1

## 2 Description

3 [Note: This method is implemented to support the `System.IComparable` interface. Note  
4 that, although a NaN is not considered to be equal to another NaN (even itself), the  
5 `System.IComparable` interface requires that `A.CompareTo (A)` return zero.

6

7 ]

## 8 Exceptions

| Exception                       | Condition  |
|---------------------------------|--|
| <b>System.ArgumentException</b> | <i>value</i> is not a null reference and is not of type <code>System.Double</code> . |

9

10

# Double.Equals(System.Double) Method

```
[ILAsm]  
.method public hidebysig virtual bool Equals(float64 obj)  
  
[C#]  
public override bool Equals(double obj)
```

## Summary

Determines whether the current instance and the specified `System.Double` represent the same value.

## Parameters

| Parameter  | Description  |
|------------|--|
| <i>obj</i> | The <code>System.Double</code> to compare to the current instance. |

## Return Value

`true` if *obj* has the same value as the current instance, otherwise `false`. If either *obj* or the current instance is a NaN and the other is not, returns `false`. If *obj* and the current instance are both NaN, positive infinity, or negative infinity, returns `true`.

## Description

[*Note:* This method is implemented to support the `System.IEquatable<Double>` interface.]

# Double.Equals(System.Object) Method

```
[ILAsm]
.method public hidebysig virtual bool Equals(object obj)

[C#]
public override bool Equals(object obj)
```

## Summary

Determines whether the current instance and the specified `System.Object` represent the same type and value.

## Parameters

| Parameter  | Description  |
|------------|--|
| <i>obj</i> | The <code>System.Object</code> to compare to the current instance. |

## Return Value

true if *obj* is a `System.Double` with the same value as the current instance, otherwise false. If *obj* is a null reference or is not an instance of `System.Double`, returns false. If either *obj* or the current instance is a NaN and the other is not, returns false. If *obj* and the current instance are both NaN, positive infinity, or negative infinity, returns true.

## Description

[Note: This method overrides `System.Object.Equals`.]

# Double.GetHashCode() Method

```
[ILAsm]  
.method public hidebysig virtual int32 GetHashCode()  
  
[C#]  
public override int GetHashCode()
```

## Summary

Generates a hash code for the current instance.

## Return Value

A `System.Int32` containing the hash code for this instance.

## Description

The algorithm used to generate the hash code is unspecified.

[*Note:* This method overrides `System.Object.GetHashCode`.]

# Double.IsInfinity(System.Double) Method

```
[ILAsm]  
.method public hidebysig static bool IsInfinity(float64 d)  
  
[C#]  
public static bool IsInfinity(double d)
```

## Summary

Determines whether the specified `System.Double` represents an infinity, which can be either positive or negative.

## Parameters

| Parameter | Description                                   |
|-----------|---|
| <i>d</i>  | The <code>System.Double</code> to be checked. |

## Return Value

`true` if *d* represents a positive or negative infinity value; otherwise `false`.

## Description

[*Note:* Floating-point operations return positive or negative infinity values to signal an overflow condition.]



# Double.IsNaN(System.Double) Method

```
[ILAsm]  
.method public hidebysig static bool IsNaN(float64 d)  
  
[C#]  
public static bool IsNaN(double d)
```

## Summary

Determines whether the value of the specified `System.Double` is undefined (Not-a-Number).

## Parameters

| Parameter | Description                                   |
|-----------|---|
| <i>d</i>  | The <code>System.Double</code> to be checked. |

## Return Value

`true` if *d* represents a NaN value; otherwise `false`.

## Description

[*Note:* Floating-point operations return NaN values to signal that the result of the operation is undefined. For example, dividing (Double) 0.0 by 0.0 results in a NaN value.]

# Double.IsNegativeInfinity(System.Double) Method

```
[ILAsm]  
.method public hidebysig static bool IsNegativeInfinity(float64 d)  
  
[C#]  
public static bool IsNegativeInfinity(double d)
```

## Summary

Determines whether the specified `System.Double` represents a negative infinity value.

## Parameters

| Parameter | Description                                   |
|-----------|---|
| <i>d</i>  | The <code>System.Double</code> to be checked. |

## Return Value

`true` if *d* represents a negative infinity value; otherwise `false`.

## Description

[*Note:* Floating-point operations return negative infinity values to signal an overflow condition.]

# Double.IsPositiveInfinity(System.Double)

## Method

```
[ILAsm]  
.method public hidebysig static bool IsPositiveInfinity(float64 d)  
  
[C#]  
public static bool IsPositiveInfinity(double d)
```

### Summary

Determines whether the specified `System.Double` represents a positive infinity value.

### Parameters

| Parameter | Description                                   |
|-----------|---|
| <i>d</i>  | The <code>System.Double</code> to be checked. |

### Return Value

true if *d* represents a positive infinity value; otherwise false.

### Description

[*Note:* Floating-point operations return positive infinity values to signal an overflow condition.]

# Double.Parse(System.String) Method

```
[ILAsm]  
.method public hidebysig static float64 Parse(string s)  
  
[C#]  
public static double Parse(string s)
```

## Summary

Returns the specified `System.String` converted to a `System.Double` value.

## Parameters

| Parameter      | Description  |
|----------------|--|
| <code>s</code> | A <code>System.String</code> containing the value to convert. The string is interpreted using the <code>System.Globalization.NumberStyles.Float</code> and/or <code>System.Globalization.NumberStyles.AllowThousands</code> style. |

## Return Value

The `System.Double` value obtained from `s`. If `s` equals `System.Globalization.NumberFormatInfo.NaNSymbol`, this method returns `System.Double.NaN`.

## Description

This version of `System.Double.Parse` is equivalent to `System.Double.Parse(s, System.Globalization.NumberStyles.Float | System.Globalization.NumberStyles.AllowThousands, null)`.

The string `s` is parsed using the formatting information in a `System.Globalization.NumberFormatInfo` initialized for the current system culture. [*Note:* For more information, see `System.Globalization.NumberFormatInfo.CurrentInfo`.]

## Exceptions

| Exception                                 | Condition                                   |
|---|---|
| <code>System.ArgumentNullException</code> | <code>s</code> is a null reference.         |
| <code>System.FormatException</code>       | <code>s</code> is not in the correct style. |

**System.OverflowException**

s represents a value that is less than `System.Double.MinValue` or greater than `System.Double.MaxValue`.

1

2

# Double.Parse(System.String, System.Globalization.NumberStyles) Method

```
[ILAsm]  
.method public hidebysig static float64 Parse(string s, valuetype  
System.Globalization.NumberStyles style)  
  
[C#]  
public static double Parse(string s, NumberStyles style)
```

## Summary

Returns the specified System.String converted to a System.Double value.

## Parameters

| Parameter    | Description  |
|--------------|--|
| <i>s</i>     | A System.String containing the value to convert. The string is interpreted using the style specified by <i>style</i> .   |
| <i>style</i> | Zero or more System.Globalization.NumberStyles values that specify the style of <i>s</i> . Specify multiple values for <i>style</i> using the bitwise OR operator. If <i>style</i> is a null reference, the string is interpreted using the System.Globalization.NumberStyles.Float and System.Globalization.NumberStyles.AllowThousands styles. |

## Return Value

The System.Double value obtained from *s*. If *s* equals System.Globalization.NumberFormatInfo.NaNSymbol, this method returns System.Double.NaN.

## Description

This version of System.Double.Parse is equivalent to System.Double.Parse (*s*, *style*, null ).

The string *s* is parsed using the formatting information in a System.Globalization.NumberFormatInfo initialized for the current system culture. [Note: For more information, see System.Globalization.NumberFormatInfo.CurrentInfo.]

## Exceptions

| Exception                           | Condition  |
|-------------------------------------|--|
| <b>System.ArgumentNullException</b> | s is a null reference.   |
| <b>System.FormatException</b>       | s is not in the correct style.   |
| <b>System.OverflowException</b>     | s represents a value that is less than <code>System.Double.MinValue</code> or greater than <code>System.Double.MaxValue</code> . |

1

2

# Double.Parse(System.String, System.IFormatProvider) Method

```
[ILAsm]  
.method public hidebysig static float64 Parse(string s, class  
System.IFormatProvider provider)  
  
[C#]  
public static double Parse(string s, IFormatProvider provider)
```

## Summary

Returns the specified `System.String` converted to a `System.Double` value.

## Parameters

| Parameter       | Description  |
|-----------------|--|
| <i>s</i>        | A <code>System.String</code> containing the value to convert. The string is interpreted using the <code>System.Globalization.NumberStyles.Float</code> and/or <code>System.Globalization.NumberStyles.AllowThousands</code> style. |
| <i>provider</i> | A <code>System.IFormatProvider</code> that supplies a <code>System.Globalization.NumberFormatInfo</code> containing culture-specific formatting information about <i>s</i> .   |

## Return Value

The `System.Double` value obtained from *s*. If *s* equals `System.Globalization.NumberFormatInfo.NaNString`, this method returns `System.Double.NaN`.

## Description

This version of `System.Double.Parse` is equivalent to `System.Double.Parse(s, System.Globalization.NumberStyles.Float | System.Globalization.NumberStyles.AllowThousands, provider)`.

The string *s* is parsed using the culture-specific formatting information from the `System.Globalization.NumberFormatInfo` instance supplied by *provider*. If *provider* is null or a `System.Globalization.NumberFormatInfo` cannot be obtained from *provider*, the formatting information for the current system culture is used.

## Exceptions



| Exception                           | Condition  |
|-------------------------------------|--|
| <b>System.ArgumentNullException</b> | s is a null reference.   |
| <b>System.FormatException</b>       | s is not in the correct style.   |
| <b>System.OverflowException</b>     | s represents a value that is less than <code>System.Double.MinValue</code> or greater than <code>System.Double.MaxValue</code> . |

1

2

# Double.Parse(System.String, System.Globalization.NumberStyles, System.IFormatProvider) Method

```
[ILAsm]  
.method public hidebysig static float64 Parse(string s, valuetype  
System.Globalization.NumberStyles style, class System.IFormatProvider  
provider)  
  
[C#]  
public static double Parse(string s, NumberStyles style, IFormatProvider  
provider)
```

## Summary

Returns the specified `System.String` converted to a `System.Double` value.

## Parameters

| Parameter       | Description   |
|-----------------|---|
| <i>s</i>        | A <code>System.String</code> containing the value to convert. The string is interpreted using the style specified by <i>style</i> .   |
| <i>style</i>    | Zero or more <code>System.Globalization.NumberStyles</code> values that specify the style of <i>s</i> . Specify multiple values for <i>style</i> using the bitwise OR operator. If <i>style</i> is a null reference, the string is interpreted using the <code>System.Globalization.NumberStyles.Float</code> and <code>System.Globalization.NumberStyles.AllowThousands</code> styles. |
| <i>provider</i> | A <code>System.IFormatProvider</code> that supplies a <code>System.Globalization.NumberFormatInfo</code> containing culture-specific formatting information about <i>s</i> .  |

## Return Value

The `System.Double` value obtained from *s*. If *s* equals `System.Globalization.NumberFormatInfo.NaNSymbol`, this method returns `System.Double.NaN`.

## Description

The string *s* is parsed using the culture-specific formatting information from the `System.Globalization.NumberFormatInfo` instance supplied by *provider*. If *provider* is null or a `System.Globalization.NumberFormatInfo` cannot be obtained from *provider*, the formatting information for the current system culture is used.

## 1 Exceptions

| Exception                           | Condition  |
|-------------------------------------|--|
| <b>System.ArgumentNullException</b> | s is a null reference  |
| <b>System.FormatException</b>       | s is not in the correct style.   |
| <b>System.OverflowException</b>     | s represents a value that is less than <code>System.Double.MinValue</code> or greater than <code>System.Double.MaxValue</code> . |

2

3

# Double.ToString(System.String, System.IFormatProvider) Method

```
[ILAsm]  
.method public final hidebysig virtual string ToString(string format,  
class System.IFormatProvider provider)  
  
[C#]  
public string ToString(string format, IFormatProvider provider)
```

## Summary

Returns a `System.String` representation of the value of the current instance.

## Parameters

| Parameter       | Description   |
|-----------------|---|
| <i>format</i>   | A <code>System.String</code> containing a character that specifies the format of the returned string, optionally followed by a non-negative integer that specifies the precision of the number in the returned <code>System.String</code> . |
| <i>provider</i> | A <code>System.IFormatProvider</code> that supplies a <code>System.Globalization.NumberFormatInfo</code> instance containing culture-specific formatting information.   |

## Return Value

A `System.String` representation of the current instance formatted as specified by *format*. The string takes into account the information in the `System.Globalization.NumberFormatInfo` instance supplied by *provider*.

## Description

If *provider* is null or a `System.Globalization.NumberFormatInfo` cannot be obtained from *provider*, the formatting information for the current system culture is used.

If *format* is a null reference, the general format specifier "G" is used.

The following table lists the format characters that are valid for the `System.Double` type.

| Format Characters | Description      |
|-------------------|------------------|
| "C", "c"          | Currency format. |

|          |                              |
|----------|------------------------------|
| "E", "e" | Exponential notation format. |
| "F", "f" | Fixed-point format.          |
| "G", "g" | General format.              |
| "N", "n" | Number format.               |
| "P", "p" | Percent format.              |
| "R", "r" | Round-trip format.           |

[*Note:* For a detailed description of formatting, see the `System.IFormattable` interface.

This method is implemented to support the `System.IFormattable` interface.

]

## Exceptions

| Exception                     | Condition                 |
|-------------------------------|---------------------------|
| <b>System.FormatException</b> | <i>format</i> is invalid. |

# Double.ToString(System.IFormatProvider) Method

```
[ILAsm]  
.method public final hidebysig virtual string ToString(class  
System.IFormatProvider provider)  
  
[C#]  
public string ToString(IFormatProvider provider)
```

## Summary

Returns a `System.String` representation of the value of the current instance.

## Parameters

| Parameter       | Description  |
|-----------------|--|
| <i>provider</i> | A <code>System.IFormatProvider</code> that supplies a <code>System.Globalization.NumberFormatInfo</code> containing culture-specific formatting information. |

## Return Value

A `System.String` representation of the current instance formatted using the general format specifier, ("G"). The string takes into account the formatting information in the `System.Globalization.NumberFormatInfo` instance supplied by *provider*.

## Description

This version of `System.Double.ToString` is equivalent to `System.Double.ToString(null, provider)`.

If *provider* is `null` or a `System.Globalization.NumberFormatInfo` cannot be obtained from *provider*, the formatting information for the current system culture is used.

[*Note:* The general format specifier formats the number in either fixed-point or exponential notation form. For a detailed description of the general format, see the `System.IFormattable` interface.]

# Double.ToString() Method

```
[ILAsm]  
.method public hidebysig virtual string ToString()  
  
[C#]  
public override string ToString()
```

## Summary

Returns a `System.String` representation of the value of the current instance.

## Return Value

A `System.String` representation of the current instance formatted using the general format specifier, ("G"). The string takes into account the current system culture.

## Description

This version of `System.Double.ToString` is equivalent to `System.Double.ToString (null, null )`.

[*Note:* The general format specifier formats the number in either fixed-point or exponential notation form. For a detailed description of the general format, see the `System.IFormattable` interface.

This method overrides `System.Object.ToString`.

]

# Double.ToString(System.String) Method

```
[ILAsm]  
.method public hidebysig instance string ToString(string format)  
  
[C#]  
public string ToString(string format)
```

## Summary

Returns a `System.String` representation of the value of the current instance.

## Parameters

| Parameter     | Description   |
|---------------|---|
| <i>format</i> | A <code>System.String</code> that specifies the format of the returned string. [ <i>Note:</i> For a list of valid values, see <code>System.Double.ToString (System.String, System.IFormatProvider )</code> .] |

## Return Value

A `System.String` representation of the current instance formatted as specified by *format*. The string takes into account the current system culture.

## Description

This version of `System.Double.ToString` is equivalent to `System.Double.ToString (format, null )`.

If *format* is a null reference, the general format specifier "G" is used.

## Exceptions

| Exception                           | Condition                 |
|-------------------------------------|---------------------------|
| <code>System.FormatException</code> | <i>format</i> is invalid. |

## Example

The following example shows the effects of various formats on the string returned by `System.Double.ToString`.

```
[C#]
```



```

1  using System;
2  class test {
3      public static void Main() {
4          double d = 1234.56789;
5          Console.WriteLine(d);
6          string[] fmts = {"C", "E", "e5", "F", "G", "N", "P", "R"};
7          for (int i=0;i<fmts.Length;i++)
8              Console.WriteLine("{0}: {1}",
9                  fmts[i],d.ToString(fmts[i]));
10     }
11 }
12
13 The output is
14
15 1234.56789
16
17
18 C: $1,234.57
19
20
21 E: 1.234568E+003
22
23
24 e5: 1.23457e+003
25
26
27 F: 1234.57
28
29
30 G: 1234.56789
31
32
33 N: 1,234.57
34
35
36 P: 123,456.79 %
37
38
39 R: 1234.56789
40
41

```