

System.EventHandler Delegate

```
[ILAsm]
.class public sealed serializable EventHandler extends System.Delegate
{.method public hidebysig newslot virtual instance void Invoke(object
sender, class System.EventArgs e) }

[C#]
public delegate void EventHandler(object sender, EventArgs e);
```

Assembly Info:

- *Name:* mscorlib
- *Public Key:* [00 00 00 00 00 00 00 00 04 00 00 00 00 00 00]
- *Version:* 2.0.x.x
- *Attributes:*
 - CLSCompliantAttribute(true)

Implements:

- **System.ICloneable**

Summary

Defines the shape of methods that are called in response to an event.

Parameters

Parameter	Description
<i>sender</i>	The object that raised the event.
<i>e</i>	A <code>System.EventArgs</code> instance that contains the event data.

Inherits From: System.Delegate

Library: BCL

Description

[*Note:* A `System.EventHandler` instance is used to specify the methods that are invoked in response to an event. To associate an instance of `EventHandler` with an event, add the `EventHandler` instance to the event. The methods referenced by the `EventHandler` instance are invoked whenever the event is raised, until the `EventHandler` instance is removed from the event.

If the event does not generate data, applications use the base class `System.EventArgs`

1 for the event data object *e*. For more information, see `System.EventArgs`. For additional
2 information about events, see Partitions I and II of the CLI Specification.
3
4]
5